



Dun Laoghaire - Rathdown County Council

Kilbogget Park Sports Pavilion,  
Engineering Report In Support of  
Planning Application

2534-DOB-XX-SI-RP-C-0001

APRIL 2026

## Document Control

Document:	Engineering Report in Support of Planning Application				
Project:	Kilbogget Park Sports Pavilion				
Client:	Dun Laoghaire Rathdown County Council				
Job Number:	DOBA2536				
File Origin:	8.0				
Document Checking:					
Author	Lisa Hanrahan			Signed:	
Issue	Date	Status	Issued to	Copies	Checked for Issue
1	21/04/2026	Planning	DLRCC	1E	

## Contents

1.	Introduction .....	4
	1.1 Existing Site .....	4
	1.2 Report Overview .....	5
2.	Surface Water Drainage .....	6
	2.1 Existing Surface Water Drainage.....	6
	2.2 Preliminary Site Investigation .....	6
	2.3 Proposed Surface Water Drainage.....	7
	2.4 GSDS Summary of Design Criterion .....	8
3.	Foul Drainage .....	10
	3.1 Existing Foul Drainage.....	10
	3.2 Irish Water Confirmation of Feasibility.....	10
	3.3 Proposed Foul Drainage.....	10
4.	Water Supply.....	11
	4.1 Existing Water Supply .....	11
	4.2 Proposed Water Supply .....	11
	4.3 Irish Water Confirmation of Feasibility.....	11
	4.4 Water Demand Calculations .....	11

### Appendices

Appendix A – Dun Laoghaire Rathdown Co. Co. / IW Drainage Maps

Appendix B – Preliminary Site Investigation Report

Appendix C – SW Calculations


## 1. Introduction

Dun Laoghaire Rathdown County Council are providing integrated design team services for a Part 8 planning application for the development of Kilbogget Sports Pavilion located in Cabinteely, County Dublin. This Engineering planning design report has been prepared by Donnachadh O'Brien & Associates Consulting Engineers (DOB&A) on behalf of Dun Laoghaire Rathdown County Council in support of the Part 8 application.

The proposed development includes a Sports Pavilion, soccer playing pitch, walkways and play areas as indicated on Dun Laoghaire Rathdown County Council.

### 1.1 Existing Site

The section of the existing park which is been developed is approx. 2 acres is bounded to the north, south and west by the athletic fields and to the east by Churchview Road. The topography of the overall land falls from north to south levels of approx. +31.47m OD to +30.93m OD. The existing site layout is indicated on drawing C-0010 while the proposed site layout is indicated on drawing C-0050. The site location is included in Figure 1 below.



**Figure 1 – Site location (highlighted in red)**

## 1.2 Report Overview

This report outlines the preliminary engineering design associated with the proposed Part 8 planning submission under the following headings:

- Surface Water Drainage
- Foul Water Drainage
- Water Supply

This report should be read in conjunction with the following engineering drawings, which are submitted in support of the planning application:

C-0010	Topographical Survey
C-0020	Proposed Surface Water Drainage Layout
C-0030	Proposed Foul Drainage and Watermain Layout
C-0120	Proposed Drainage details

## 2. Surface Water Drainage

### 2.1 Existing Surface Water Drainage


An existing local surface water drainage network has been identified around the existing buildings which are included in the application boundary. This network discharges to the public surface water network on Churchview Road to the east of the application site. A local surface water network has also been identified around the perimeter of the existing all-weather pitch which also appears to be discharging towards the Churchview Road (subject to further CCTV surveys).

An existing 600mm diameter SW pipe has been identified along Churchview Road based on the topographical survey information.

### 2.2 Preliminary Site Investigation

IGSL were previously commissioned by DOB&A on behalf of Dun Laoghaire Rathdown County Council to carry out preliminary site investigations including trial pits and soakaway tests (refer to Appendix B for the full report - 21490) in the vicinity of the proposed works. The previous infiltration tests failed due to the impermeable nature of the cohesive subsoils. An extract of the infiltration tests carried out previously is included in Figure XX below.

**DONNACHADH O'BRIEN**  
& ASSOCIATES CONSULTING ENGINEERS



**Figure 2** Extract from infiltration test results IGSL report 21490

Supplementary site investigations have been procured by DOBA on behalf of DLRCC and will be carried out prior to commencement of the works.

### 2.3 Proposed Surface Water Drainage

The design and management of surface water for the proposed development will comply with the policies and guidelines of Dun Laoghaire Rathdown County Council and outlined in the Greater Dublin Strategic Drainage Study (GSDSDS) and Sustainable Drainage Systems (SuDS) Strategy. Pipe sizes and gradients will be designed to achieve self-cleansing velocities as per the requirements of the Building Regulations Part “H”.

The layout of the proposed surface water drainage is included on the following drawings:

C-0020 Proposed Surface Water Drainage Layout

### 2.3.1 SuDS Measures

Infiltration measures have been utilised where favourable infiltration rates have been identified in the site investigation report. The surface water strategy includes the following:

- A Blue Roof is to be incorporated on the proposed new building. This will store the rainfall runoff for storm events up to a 1% AEP event plus 30% climate change with a discharge restricted to Qbar.
- The runoff from the proposed all-weather pitch will be restricted to Qbar, via a hydrobrake, and volumes up to a 1% AEP event plus 30% climate change will be stored in filter drains along the pitch;
- The playground areas and paths are to be constructed using permeable materials to reflect the pre-development greenfield characteristics;
- Maintenance of the filter drains will be via a rigid perforated pipe installed within the trench with a silt trap manhole provided at each end;

### 2.4 GSDS Summary of Design Criterion

GSDS summarises the design criteria for the design of drainage systems under four criterions in Section 6.3.4 as follows:

1. Criterion 1 – River water quality protection
2. Criterion 2 – River regime protection
3. Criterion 3 – Level of service (Flooding) for the site
4. Criterion 4 – River flood protection

#### 2.4.1 Criterion 1 – River water quality protection

The green / blue roof will provide adequate interception of rainfall. The first 5mm of rainfall event on site the pitch will be intercepted without discharging within the filter drains serving the pitch.

#### 2.4.2 Criterion 2 – River regime protection

Discharge from the site will be via a Hydrobrake to the existing public network located on Churchview Road.

**2.4.3 Criterion 3 – Level of service (Flooding) for the site**

The filter drains on site has been designed to store volumes up to 1 in 100 - year rainfall event + 30% climate change below ground with no flooding on the site proposed.

**2.4.4 Criterion 4 – River flood protection**

Long term storage of runoff is not proposed due to the extremely poor infiltration results. The discharge is restricted to Qbar with storage of storm events up to a 1& AEP event + 30% climate change to provide river flood protection.

## 3. Foul Drainage

### 3.1 Existing Foul Drainage

Dun Laoghaire Rathdown County Council and Irish Water records indicate an existing 225mm diameter foul sewer adjacent to the sports Pavilion on Churchview Road which serves the Kilbogget Park.

Dun Laoghaire Rathdown County Council and Irish Water maps are included in Appendix A of this report.

### 3.2 Irish Water Confirmation of Feasibility

A pre connection enquiry was submitted to Irish Water for a wastewater connection for the proposed development. We have yet to receive feedback from Irish Water.

### 3.3 Proposed Foul Drainage

The proposed foul network will collect effluent from the new community building via a piped gravity network which will discharge to the existing foul manhole located at the north east boundary of the site. The design of the new foul network will be in compliance with the Irish Water Code of Practice and Standard Details for Wastewater Infrastructure.

The proposed discharge from the future community buildings connecting into the existing foul public network has been calculated in accordance with Irish Water standards using a peak flow factor of 4.5DWF.

Estimated Maximum Occupancy = 50 persons (Conservative)

Average Daily Discharge =  $(50 \times 40 \text{ l/person/day}) / (24 \times 60 \times 60) = 0.023 \text{ l/s}$

Average Daily Discharge x infiltration = 0.0255 l/s

Peak Daily Discharge =  $0.08 \times 6 \text{ DWF} = 0.1146 \text{ l/s}$

The layout of the proposed foul water drainage is included on drawing C-0030 (Proposed Foul Drainage and Watermain Layout).

## 4. Water Supply

### 4.1 Existing Water Supply

Dun Laoghaire Rathdown County Council and Irish Water records indicate an existing 150mm uPVC public water serving the Kilbogget Park running through the centre of the site. Dun Laoghaire Rathdown County Council and Irish Water maps are included in Appendix A of this report.

### 4.2 Proposed Water Supply

It is proposed to keep the existing watermain and extend it to loop around the new building.

The layout of the proposed water main is included on the following drawings:

C-0030	Proposed Foul Drainage and Watermain Layout
C-0130	Typical Watermain Details

### 4.3 Irish Water Confirmation of Feasibility

A pre connection enquiry was submitted to Irish Water for new water connection for the proposed application development. . We have yet to receive feedback from Irish Water.

### 4.4 Water Demand Calculations

Estimate Occupancy = 50 persons


Consumption = 40 litres / person / day x 50 persons = 2,000litres / day

Average Daily Demand = 2,000 litres / day x 1.25 = 2,5000 l / day/ (24x60x60) = 0.03 litres / second

Peak Daily Demand = 0.03 x 5 = 0.1446 litres / second

## Appendix A – Drainage Maps





© Ordnance Survey Ireland | © Ordnance Survey Ireland |

Reproduced from the Ordnance Survey Of Ireland by Permission of the Government. License No. 3-3-34

© Ordnance Survey Ireland


11/5/2018 12:34:58 PM

<b>Legend</b>					
<b>Stormwater Gravity Mains (Irish Water Owned)</b>		<b>LH</b> Lamphole	<b>Storm Fittings</b>	<b>---</b> Storm Culverts	<b>Sewer Gravity Mains (Non-Irish Water owned)</b>
	Surface		Vent/Col	Storm Clean Outs	
<b>Stormwater Gravity Mains (Non-Irish Water Owned)</b>				<b>Sewer Gravity Mains (Irish Water owned)</b>	
	Surface	<b>Storm Inlets</b>	<b>Storm Discharge Points</b>		
<b>Storm Manholes</b>		Gully	Outfall		
	Cascade				
	Catchpit				
	Hatchbox				

Irish Water gives this information as to the position of its underground network as a general guide only on the strict understanding that it is based on the best available information provided by each Local Authority in Ireland. It should not be relied upon in the event of excavations or other works being carried out in the vicinity of the network. The onus is on the parties carrying out the works to ensure the exact location of the network is identified prior to mechanical works being carried out. Service pipes are not generally shown but their presence should be anticipated. © Irish Water



"Gas Networks Ireland (GNI), their affiliates and assigns, accept no responsibility for any information contained in this document concerning location and technical designation of the gas distribution and transmission network ("the Information"). Any representations and warranties express or implied, are excluded to the fullest extent permitted by law. No liability shall be accepted for any loss or damage including, without limitation, direct, indirect, special, incidental, punitive or consequential loss including loss of profits, arising out of or in connection with the use of the Information (including maps or mapping data). NOTE: DIAL BEFORE YOU DIG Phone 1850 427 747 or e-mail dig@gasnetworks.ie - The actual position of the gas/electricity distribution and transmission network must be verified on site before any mechanical excavating takes place. If any mechanical excavation is proposed, hard copy maps must be requested from GNI re gas. All work in the vicinity of the gas distribution and transmission network must be completed in accordance with the current edition of the Health & Safety Authority publication, 'Code of Practice For Avoiding Danger From Underground Services' which is available from the Health and Safety Authority (1890 28 93 89) or can be downloaded free of charge at www.hsa.ie."



Reproduced from the Ordnance Survey of Ireland by Permission of the Government. License No. 3-3-34

© Ordnance Survey Ireland

11/5/2018 12:38:19 PM

<b>Legend</b>					
<b>Stormwater Gravity Mains (Irish Water Owned)</b>		<b>LH</b> Lamphole	<b>Storm Fittings</b>	<b>---</b> Storm Culverts	<b>Sewer Gravity Mains (Non-Irish Water owned)</b>
Surface	Standard	Vent/Col	Storm Clean Outs	Combined	Foul
<b>Stormwater Gravity Mains (Non-Irsh Water Owned)</b>		<b>OTHER</b> Other; Unknown	<b>OTHER</b> Other; Unknown	<b>Sewer Gravity Mains (Irish Water owned)</b>	Overflow
Surface	Other; Unknown	<b>Storm Discharge Points</b>		Combined	Unknown
<b>Storm Manholes</b>		Gully	Outfall	Foul	Overflow
Cascade	Standard	Overflow	Soakaway	Unknown	Other; Unknown
Catchpit	Other; Unknown	Other; Unknown			
Hatchbox					

Irish Water gives this information as to the position of its underground network as a general guide only on the strict understanding that it is based on the best available information provided by each Local Authority in Ireland. It should not be relied upon in the event of excavations or other works being carried out in the vicinity of the network. The onus is on the parties carrying out the works to ensure the exact location of the network is identified prior to mechanical works being carried out. Service pipes are not generally shown but their presence should be anticipated. © Irish Water



"Gas Networks Ireland (GNI), their affiliates and assigns, accept no responsibility for any information contained in this document concerning location and technical designation of the gas distribution and transmission network ("the Information"). Any representations and warranties express or implied, are excluded to the fullest extent permitted by law. No liability shall be accepted for any loss or damage including, without limitation, direct, indirect, special, incidental, punitive or consequential loss including loss of profits, arising out of or in connection with the use of the Information (including maps or mapping data). NOTE: DIAL BEFORE YOU DIG Phone 1850 427 747 or e-mail dig@gasnetworks.ie - The actual position of the gas/electricity distribution and transmission network must be verified on site before any mechanical excavating takes place. If any mechanical excavation is proposed, hard copy maps must be requested from GNI re gas. All work in the vicinity of the gas distribution and transmission network must be completed in accordance with the current edition of the Health & Safety Authority publication, 'Code of Practice For Avoiding Danger From Underground Services' which is available from the Health and Safety Authority (1890 28 93 89) or can be downloaded free of charge at www.hsa.ie."

## Appendix B –Preliminary Site Investigation Report

**DEVELOPMENT  
AT KILGOBBET PARK  
CABINTEELY  
(DLR Co.Co.)**

---

**DONNACHADH O'BRIEN  
CONSULTING ENGINEERS**

## **CONTENTS**

<b>I</b>	<b>INTRODUCTION</b>
<b>II</b>	<b>FIELDWORK</b>
<b>III</b>	<b>TESTING</b>
<b>III</b>	<b>DISCUSSION / SUMMARY</b>

## **APPENDICES**

<b>I</b>	<b>BORING RECORD</b>
<b>II</b>	<b>TRIAL PIT LOGS</b>
<b>III</b>	<b>DYNAMIC PROBES</b>
<b>IV</b>	<b>PLATE BEARING TESTS</b>
<b>V</b>	<b>BRE DIGEST 365</b>
<b>VI</b>	<b>LABORATORY</b>
	<b>a. Geotechnical</b>
	<b>b. Environmental</b>
<b>VII</b>	<b>SITE PLAN</b>

## **FOREWORD**

The following Conditions and Notes on Site Investigation Procedures should be read in conjunction with this report.

### **General.**

Recommendations made, and opinions expressed in the report are based on the strata observed in the exploratory holes, together with the results of in-situ and laboratory tests. No responsibility can be held for conditions which have not been revealed by exploratory work, or which occur between exploratory hole locations. Whilst the report may suggest the likely configuration of strata, both between exploratory hole locations, or below the maximum depth of the investigation, this is only indicative, and liability cannot be accepted for its accuracy.

Unless specifically stated, no account has been taken of possible subsidence due to mineral extraction below or close to the site.

### **Boring Procedures.**

Unless otherwise stated, the 'Shell and Auger' technique of soft ground boring has been employed. All boring operations sampling and/or logging of soils and in-situ testing complies with the recommendations of the British Standard Code of Practice BS 5930 (1981), 'Site Investigation' and BS 1377:1990, 'Methods of test for soils for civil engineering purposes'.

Whilst the technique allows the maximum data to be obtained in soft ground, some disturbance and variation of soft and layered soils is unavoidable. Attention is drawn to this condition, whenever it is suspected. Where cobbles and boulders are recorded, no conclusion should be drawn concerning the size, presence, lithological nature, or numbers per unit volume of ground.

Where peat has been encountered during siteworks, samples have been logged in accordance with the Von Post Classification (ref. Von Post, L. 1992. Sveriges Geologiska Undersöknings torvinventering och nogra av dess hittills vunna resultat (SGU peat inventory and some preliminary results) Svenska Mosskulturforeningens Tidskrift, Jonkoping, Swedden, 36, 1-37 & Hobbs N. B. Mire morphology and the properties of some British and foreign peats. QJEG, Vol. 19, 1986).

**Routine Sampling.**

Undisturbed samples of soils, predominantly cohesive in nature are obtained unless otherwise stated by a 104mm diameter open-drive tube sampler. In granular soils, and where undisturbed sampling is inappropriate, disturbed samples are collected. Smaller disturbed samples are also recovered at intervals to allow a visual examination of the full strata section.

**In-Situ Testing.**

Standard penetration tests, utilising either the standard split spoon sampler or solid cone and automatic trip-hammer are conducted unless otherwise where required by instruction. Subsequent to a seating drive of 150mm, a summation for the number of blows for 300mm penetration is recorded on the boring records together with the blow count for each 75mm penetration. In cases where incomplete penetration is obtained, the number of blows for the recorded value of penetration are noted. In coarse granular soils, a cone end is fitted to the sampler and a similar procedure adopted.

**Groundwater.**

The depth of entry of any influx of groundwater is recorded during the course of boring operations. However, the normal rate of boring does not usually permit the recording of an equilibrium level for any one water strike. Where possible drilling is suspended for a period of twenty minutes to monitor the subsequent rise in water level.

Groundwater conditions observed in the borings or pits are those appertaining to the period of investigation. It should be noted however, that groundwater levels are subject to diurnal, seasonal and climatic variations and can also be affected by drainage condition, tidal variation or other causes.

**Retention of Samples.**

After satisfactory completion of all the scheduled laboratory tests on any sample, the remaining material is discarded unless a period of retention of samples is agreed, it is our normal practice to discard all soil samples one month after submission of our final report.

**REPORT ON A SITE INVESTIGATION  
FOR A PROPOSED DEVELOPMENT  
AT KILBOGGET PARK  
CABINTEELY**

**FOR  
DONNACHADH O'BRIEN AND ASSOCIATES  
CONSULTING ENGINEERS**

**Report No. 21490**

**MARCH 2019**

**I Introduction**

A new development is proposed for Kilbogget Park in Cabinteely, Co. Dublin.

An investigation of sub soil conditions in the area of the new development has been carried out by IGSL for DOBA Consulting Engineers, on behalf of Dun Laoghaire Rathdown Co.Co.

The sub soils at four specific areas located in the vicinity of the existing car park were established.

The scheduled site investigation included the following elements:

- \* Cable Percussion Borehole 1 nr.
- Trial Pit Excavations 4 nr.
- HD Dynamic Probes 4 nr.
- CBR by Plate Test 4 nr.
- BRE Digest 365 Percolation 3 nr.
- Geotechnical Laboratory Testing
- Environmental Laboratory Testing

This report includes all factual data from field operations and laboratory and discusses these findings relative to the proposed new development.

## **II Fieldwork**

The development is to take place in and around the existing Kilbogget Park car park, located off Churchview Road in Cabinteely.

The site and the proposed exploratory locations are noted on the drawing and aerial map enclosed in Appendix VII. The drawing was provided by DOBA. The investigation was concentrated in four areas referenced 1 to 4.

The various elements of the investigation are detailed in the following paragraphs. All field works were supervised by an experienced geotechnical engineer who carefully recorded stratification, recovered samples as required and prepared detailed records.

Each location was scanned electronically (CAT) to ensure that existing services were not damaged. A shallow trial pit was opened at BH01 to confirm this.

### ***Borehole***

One exploratory borehole was constructed in Area 2. The initial borehole refused on an obstruction in clay FILL at 2.00 metres BGL. A re-bore identified FILL material to a depth of 2.60 metres, overlying very stiff brown very gravelly CLAY (Boulder Clay). The borehole was terminated at 3.30 metres on obstruction. The final refusal depth is not indicative of rock horizon. No ground water was observed in this location. Detailed boring records are presented in Appendix I.

### ***Trial Pits***

Pits were excavated using a JCB excavator under engineering supervision. Detailed trial pit logs with photographs are enclosed in Appendix II.

TP01 encountered CLAY fill to a depth of 0.80 metres overlying firm to stiff gravelly SILT/CLAY (boulder clay). The excavation was completed at 2.60 metres. No ground water was noted.

TP02 noted variable FILL material to a depth of 1.80 metres with firm damp gravelly CLAY from 1.80 to 2.80 metres. Very stiff gravelly SILT/CLAY is present from 2.80 to refusal at 2.90 metres. Water ingress was noted at 2.40 metres BGL.

TP03 penetrated FILL material from GL to 3.50 metres. The fill is very variable containing domestic waste material with a distinct gassy rotten egg odour. The excavation was unstable in the damp fill material.

At TP04 variable FILL was noted to a depth of 1.40 metres overlying soft brown sandy gravelly SILT/CLAY. Excavation was terminated at 3.00 metres with water noted at 2.30 metres and excavation instability recorded.

## ***Dynamic Probes***

Heavy Duty Dynamic Probes were taken at the four investigation locations. Probing was in accordance with the heavy-duty probe specification of BS 1377: Part 9: 1990. In these tests, the soil resistance is measured in terms of the number of drop-hammer blows required to drive the test probe through each 100 mm increment of penetration. Probing is terminated when the blow count exceeds 25/100mm to avoid damage to the apparatus. Where loose material is present a single blow count may drive the apparatus in excess of 100mm. In this instance blow counts of zero may be recorded.

Individual probe records are contained in Appendix III.

The probe graphs generally reflect a pattern of soft or firm soils to depths ranging from 1.50 to 3.50 metres. This would typically be related to probe resistance less than  $N_{100} = 3$ .

Increasing resistance, reflecting base stiff boulder clay was noted as follows:

DP01	3.20
DP02	2.30
DP03	2.50
DP04	3.50

## ***In Situ CBR by Plate Bearing Test***

The CBR value of the soils at shallow depth was established at three locations using Plate Bearing Test Apparatus. Tests were carried out along the line of the proposed site access road. A steel plate is loaded and off-loaded incrementally over two stages and the deflection under load and recovery under off-load is measured by a system of dial gauges. The data is processed and load settlement graphs are prepared. An equivalent CBR value is calculated in accordance with NRA HD25-26/10. At each location testing was carried out on FILL material.

Results are summarised in the following table and details are presented in Appendix IV

<b>Test No.</b>	<b>Depth</b>	<b>CBR at Load Cycle (%)</b>	<b>CBR @ Re-Load (%)</b>
PBT 01	0.50	1.2	2.7
PBT 02	0.40	2.9	8.5
PBT 03	0.40	1.9	6.1
PBT 04	0.40	1.4	4.3

### *c. Percolation Test / BRE DIGEST 365*

Infiltration testing was performed at three of the four locations in accordance with BRE Digest 365 'Soakaway Design'. No test was performed at location 3.

To obtain a measure of the infiltration rate of the sub-soils, water is poured into the test pits, and records taken of the fall in water level against time. The tests are carried over two cycles following initial soakage. Designs are based on the slowest infiltration rate, which is generally calculated from the final cycle.

The infiltration rate is the volume of water dispersed per unit exposed area per unit of time, and is generally expressed as metres/minute or metres/second. In these calculations the exposed area is the sum of the base area and the average internal area of the pit sides over the test duration.

In all three locations no fall in water level was observed, the tests are therefore classed as failures. The results are typical of the extremely low permeability gravelly clay forming the FILL deposits over the site area.

Full details of each test are contained in Appendix V.

### **III. Laboratory Testing**

A programme of laboratory testing was scheduled following completion of site operations. Geotechnical testing was carried out by IGSL in its INAB-Accredited laboratory. Environmental and chemical testing was carried out in the UK by CHEMTEST Ltd. The test programme included the following elements:

- Liquid and Plastic Limits / Moisture Content
- PSD Grading by wet sieve and hydrometer.
- Sulphate and pH
- RILTA Suite

Individual test results are discussed in the following paragraphs.

#### *Classification*

Three cohesive samples from the trial pits had index properties established. Test results for the soils confirm clay or silt matrix material in the CI zone of the standard classification. One sample from TP02 is defined as very silty gravelly SAND.

### *Grading*

Wet sieve with hydrometer analysis as necessary was used to establish PSD grading curves for three samples selected.

Two samples conform to the normal boulder clay pattern with smooth grading from the clay to gravel fraction.

The sample from TP02 is confirmed as brown silty very gravelly SAND.

### *Sulphate and pH.*

Two samples were selected for sulphate and pH analysis. Sulphate concentrations (SO<sub>4</sub> 2:1 extract) of < 0.010 g/l were established with pH values of 8.3 and 7.9 . No special precautions are necessary to protect foundation concrete from sulphate aggression. A sulphate design class of DS-1 (ACEC Classification for Concrete) is indicated for concentrations less than 0.5 g/l.

### *Environmental*

Four soil samples were submitted for detailed environmental analysis to RILTA (WAC) parameters. The results confirm that the material can be classified as INERT with no elevated contaminant levels recorded. The results indicate that material excavated from this site can be readily disposed of either on-site or to a licensed landfill facility.

No asbestos traces were found during routine screening.

While the RILTA Suite tests indicate INERT classification it should be noted that the fill at TP03 contained what appears to be household waste with a rotten egg odour indicative of landfill gas generation noted by the field engineer.

## **IV. Discussion:**

The new development is to be carried out at the main car park area located off Churchview Road.

A detailed investigation has been carried out under the direction of DOBA. The factual data from field and laboratory is presented in Sections I to III of this report.

Four distinct areas were examined and the findings can be summarised as follows:

	Area 1	Area 2	Area 3	Area 4
Made Ground	0 – 0.80	0 – 1.80	0 – 3.50	0 -1.40
Soft to Firm Clay	0.80 – 2.50	1.80 – 2.80	N/A	1.40 – 3.00
Stiff boulder Clay	2.50 – 2.80	2.80 – 2.90	N/A	N/A
Stiff Soils defined by Probe N <sub>100</sub> = 5	3.10	2.40	2.70	3.50
Ground Water (m BGL)	Dry	2.40	0.70	2.30
Percolation	Fail	Fail	N/A	Fail
CBR (Load) %	1.2	2.9	1.9	1.4
(Re-load) %	2.7	8.5	6.1	4.3

### ***New Foundations***

The fill deposits and underlying soft soils are unsuited as founding medium.

Foundations for new structures in the area should therefore be taken to the stiff boulder clay encountered in all locations at depths ranging from 2.40 to 3.50 metres. Either direct excavation or piled foundations can be considered.

If direct excavation is employed note should be taken of excavation instability and ground water. Statutory safety regulations prohibit personnel entering unsupported excavations deeper than 1.20 metres, irrespective of apparent stability.

### ***Pavements / Storm Water Disposal***

CBR values at each of the four locations are noted above and can be utilised for pavement design.

The soils are not suited for dispersion of storm or surface water, consideration should be given to the use of the local authority drainage system or of disposal to a local watercourse.

### ***Environmental***

While samples for RILTA analysis were classified as inert, the fill at TP03 contained material generating possible landfill gas. Further investigation in this area possibly by Window Sampling and Standpipe Installation followed by gas monitoring is advised.

## **Appendix I Boring Records**



# GEOTECHNICAL BORING RECORD

REPORT NUMBER

21490

<b>CONTRACT</b> Kilbogget Park, Cabinteely, Dublin		<b>BOREHOLE NO.</b> BH01
<b>CO-ORDINATES</b>		<b>SHEET</b> Sheet 1 of 1
<b>GROUND LEVEL (m AOD)</b>	<b>RIG TYPE</b> Dando 2000	<b>DATE COMMENCED</b> 21/01/2019
	<b>BOREHOLE DIAMETER (mm)</b>	<b>DATE COMPLETED</b> 21/01/2019
	<b>BOREHOLE DEPTH (m)</b> 2.00	
<b>CLIENT</b> Dun Laoghaire Rathdown Co. Co.	<b>SPT HAMMER REF. NO.</b>	<b>BORED BY</b> P.Allan
<b>ENGINEER</b> DOB	<b>ENERGY RATIO (%)</b>	<b>PROCESSED BY</b> F.C

Depth (m)	Description	Legend	Elevation	Depth (m)	Samples				Field Test Results	Standpipe Details
					Ref. Number	Sample Type	Depth (m)	Recovery		
0	TOPSOIL			0.20						
	MADE GROUND (Comprised of brown sandy gravelly clay fill)				AA103042	B	0.50			
1	MADE GROUND (Comprised of grey/black gravelly clay fill)			1.00						
					AA103043	B	1.50		N = 34 (4, 6, 8, 8, 8, 10)	
2	Obstruction End of Borehole at 2.00 m			2.00					N = 50/150 mm (15, 18, 40, 10)	
3										
4										
5										
6										
7										
8										
9										

HARD STRATA BORING/CHISELLING				WATER STRIKE DETAILS					
From (m)	To (m)	Time (h)	Comments	Water Strike	Casing Depth	Sealed At	Rise To	Time (min)	Comments
1.7	2	2							No water strike

INSTALLATION DETAILS					Date	Hole Depth	Casing Depth	Depth to Water	Comments
Date	Tip Depth	RZ Top	RZ Base	Type					

**REMARKS** CAT scanned location and hand dug inspection pit carried out . Obstruction encountered at 2.00m . Relocated to BH01A and attempted rebore.

**Sample Legend**

- D - Small Disturbed (tub)
- B - Bulk Disturbed
- LB - Large Bulk Disturbed
- Env - Environmental Sample (Jar + Vial + Tub)
- UT - Undisturbed 100mm Diameter Sample
- P - Undisturbed Piston Sample
- W - Water Sample

IGSSL BH LOG 21490.GPJ IGSSL.GDT 24/1/19



# GEOTECHNICAL BORING RECORD

REPORT NUMBER

21490

<b>CONTRACT</b> Kilbogget Park, Cabinteely, Dublin		<b>BOREHOLE NO.</b> BH01A
<b>CO-ORDINATES</b>		<b>SHEET</b> Sheet 1 of 1
<b>GROUND LEVEL (m AOD)</b>	<b>RIG TYPE</b> Dando 2000	<b>DATE COMMENCED</b> 22/01/2019
	<b>BOREHOLE DIAMETER (mm)</b>	<b>DATE COMPLETED</b> 22/01/2019
	<b>BOREHOLE DEPTH (m)</b> 3.30	
<b>CLIENT</b> Dun Laoghaire Rathdown Co. Co.	<b>SPT HAMMER REF. NO.</b>	<b>BORED BY</b> P.Allan
<b>ENGINEER</b> DOB	<b>ENERGY RATIO (%)</b>	<b>PROCESSED BY</b> F.C.

Depth (m)	Description	Legend	Elevation	Depth (m)	Samples				Field Test Results	Standpipe Details
					Ref. Number	Sample Type	Depth (m)	Recovery		
0	TOPSOIL			0.20						
1	MADE GROUND (Comprised of brown sandy gravelly clay fill)			1.50	AA101709	B	1.00		N = 35 (3, 7, 9, 7, 8, 11)	
2	MADE GROUND (Comprised of grey/black sandy gravelly clay fill)			2.60	AA101710	B	2.00			
3	Hard brown gravelly CLAY with cobbles			3.30	AA101711	B	3.00		N = 50/150 mm (20, 5, 40, 10)	
3.30	Obstruction End of Borehole at 3.30 m									

HARD STRATA BORING/CHISELLING				WATER STRIKE DETAILS					
From (m)	To (m)	Time (h)	Comments	Water Strike	Casing Depth	Sealed At	Rise To	Time (min)	Comments
3	3.3	2							No water strike

INSTALLATION DETAILS					Date	Hole Depth	Casing Depth	Depth to Water	Comments
Date	Tip Depth	RZ Top	RZ Base	Type					

**REMARKS** CAT scanned location and hand dug inspection pit carried out. Obstruction encountered at 2.00m. Relocated to BH01A and attempted rebore.

**Sample Legend**  
 D - Small Disturbed (tub)  
 B - Bulk Disturbed  
 LB - Large Bulk Disturbed  
 Env - Environmental Sample (Jar + Vial + Tub)  
 UT - Undisturbed 100mm Diameter Sample  
 P - Undisturbed Piston Sample  
 W - Water Sample

IGSL BH LOG 21490.GPJ IGSL.GDT 24/1/19

## **Appendix II Trial Pit Records**



# TRIAL PIT RECORD

REPORT NUMBER

21490

<b>CONTRACT</b> Kilbogget Park, Cabinteely, Dublin		<b>TRIAL PIT NO. SHEET</b> TP01 Sheet 1 of 1	
<b>LOGGED BY</b> L. Daniels	<b>CO-ORDINATES</b> 724,205.00 E 724,807.00 N		<b>DATE STARTED</b> 16/01/2019
<b>CLIENT</b> Dun Laoghaire Rathdown Co. Co.	<b>GROUND LEVEL (m)</b>		<b>DATE COMPLETED</b> 16/01/2019
<b>ENGINEER</b> DOB			<b>EXCAVATION METHOD</b> JCB

Depth (m)	Geotechnical Description	Legend	Depth (m)	Elevation	Water Strike	Samples			Vane Test (KPa)	Hand Penetrometer (KPa)
						Sample Ref	Type	Depth		
0.0	TOPSOIL (MADE GROUND)									
0.20	Soft to firm brown slightly sandy gravelly SILT/CLAY (MADE GROUND)		0.20							
0.80	Firm brown slightly gravelly SILT/CLAY with a medium cobble content and low boulder content (<350mm). (Possible MADE GROUND)		0.80			AA110726	Env B	0.50 0.50		
1.50			1.50			AA110727	Env B	1.50 1.50		
2.50	Stiff brown gravelly CLAY with a medium cobble content and a low boulder content (<350mm)		2.50							
2.60	End of Trial Pit at 2.60m		2.60							

**Groundwater Conditions**  
Dry

**Stability**  
Stable

**General Remarks**

IGSL TP LOG 21490.GPJ IGSL.GDT 24/1/19



# TRIAL PIT RECORD

REPORT NUMBER

21490

<b>CONTRACT</b> Kilbogget Park, Cabinteely, Dublin	<b>TRIAL PIT NO.</b> TP02
	<b>SHEET</b> Sheet 1 of 1
<b>LOGGED BY</b> L. Daniels	<b>CO-ORDINATES</b> 724,165.00 E 724,908.00 N
	<b>DATE STARTED</b> 16/01/2019
<b>CLIENT</b> Dun Laoghaire Rathdown Co. Co.	<b>DATE COMPLETED</b> 16/01/2019
<b>ENGINEER</b> DOB	<b>GROUND LEVEL (m)</b>
	<b>EXCAVATION METHOD</b> JCB

Depth (m)	Geotechnical Description	Legend	Depth (m)	Elevation	Water Strike	Samples			Vane Test (KPa)	Hand Penetrometer (KPa)
						Sample Ref	Type	Depth		
0.0	TOPSOIL (MADE GROUND)									
0.20	Soft to firm brown slightly sandy gravelly CLAY with a medium cobble content and a low boulder content (<250mm). Infrequent brick fragments, concrete fragments, granite fragments (MADE GROUND)		0.20							
0.50			0.50			AA110717	Env B	0.50		
0.90	Soft to firm dark brown slightly gravelly CLAY. Frequent timber, rootlets (MADE GROUND)		0.90							
1.00			1.00			AA110718	Env B	1.00		
1.80	Firm wet greyish brown very sandy gravelly CLAY		1.80		↓ (Seepage)					
2.00			2.00			AA110719	Env B	2.00		
2.80	Stiff brown gravelly SILT/CLAY with a low cobble content		2.80		↓ (Moderate)					
2.90			2.90							
3.0	End of Trial Pit at 2.90m									

**Groundwater Conditions**  
Groundwater at 2.40m

**Stability**  
Wall collapse from 1.50m to end of pit

**General Remarks**

IGSL TP LOG 21490.GPJ IGSL.GDT 24/1/19



# TRIAL PIT RECORD

REPORT NUMBER

21490

<b>CONTRACT</b> Kilbogget Park, Cabinteely, Dublin	<b>TRIAL PIT NO.</b> TP03
	<b>SHEET</b> Sheet 1 of 1
<b>LOGGED BY</b> L. Daniels	<b>CO-ORDINATES</b> 724,108.00 E 724,864.00 N
	<b>DATE STARTED</b> 16/01/2019
	<b>DATE COMPLETED</b> 16/01/2019
<b>CLIENT</b> Dun Laoghaire Rathdown Co. Co.	<b>GROUND LEVEL (m)</b>
<b>ENGINEER</b> DOB	<b>EXCAVATION METHOD</b> JCB

Depth (m)	Geotechnical Description	Legend	Depth (m)	Elevation	Water Strike	Samples			Vane Test (KPa)	Hand Penetrometer (KPa)
						Sample Ref	Type	Depth		
0.0	TOPSOIL (MADE GROUND)	[Cross-hatch pattern]								
	Brown slightly sandy gravelly CLAY (MADE GROUND)		0.20							
	Very soft to soft black sludgy silty clayey GRAVEL with abundant waste material including plastic bags and tape, concrete fragments, granite fragments, cloth, bedsprings, rotten egg odour (MADE GROUND)		0.70			AA110720	Env B	0.50 0.50		
1.0						AA110721	Env B	1.00 1.00		
2.0					AA110722	Env B	2.00 2.00			
3.0										
	End of Trial Pit at 3.50m		3.50							
4.0										

**Groundwater Conditions**  
Damp from 0.70m

**Stability**  
Wall collapse from 0.70m to end of pit

**General Remarks**

IGSL TP LOG 21490.GPJ IGSL.GDT 24/1/19



# TRIAL PIT RECORD

REPORT NUMBER

21490

<b>CONTRACT</b> Kilbogget Park, Cabinteely, Dublin	<b>TRIAL PIT NO.</b> TP04
	<b>SHEET</b> Sheet 1 of 1
<b>LOGGED BY</b> L. Daniels	<b>CO-ORDINATES</b> 724,135.00 E 724,819.00 N
<b>CLIENT</b> Dun Laoghaire Rathdown Co. Co.	<b>DATE STARTED</b> 16/01/2019
<b>ENGINEER</b> DOB	<b>DATE COMPLETED</b> 16/01/2019
	<b>EXCAVATION METHOD</b> JCB

Depth (m)	Geotechnical Description	Legend	Depth (m)	Elevation	Water Strike	Samples			Vane Test (KPa)	Hand Penetrometer (KPa)
						Sample Ref	Type	Depth		
0.0	TOPSOIL (MADE GROUND)		0.20							
	Brown slightly sandy gravelly CLAY. Infrequent cloth, plastic, timber fragments (MADE GROUND)									
1.0			1.40							
	Soft brown sandy slightly gravelly SILT/CLAY									
2.0			3.00		↓ (Moderate)					
	End of Trial Pit at 3.00m									
3.0										
4.0										

**Groundwater Conditions**  
Groundwater at 2.30m

**Stability**  
Wall collapse from 1.60m to end of pit

**General Remarks**

**21490: Kilboggett Park, Cabinteely. Trial Pits.**



TP01

**21490: Kilboggett Park, Cabinteely. Trial Pits.**



TP01 Spoil

**21490: Kilboggett Park, Cabinteely. Trial Pits.**



TP02

## 21490: Kilboggett Park, Cabinteely. Trial Pits.



TP02 Spoil

**21490: Kilboggett Park, Cabinteely. Trial Pits.**



TP03

## 21490: Kilboggett Park, Cabinteely. Trial Pits.



TP03 Spoil

**21490: Kilboggett Park, Cabinteely. Trial Pits.**



TP04

## 21490: Kilboggett Park, Cabinteely. Trial Pits.



TP04 Spoil

## **Appendix III Dynamic Probes**



# DYNAMIC PROBE RECORD

REPORT NUMBER

21490

<b>CONTRACT</b> Kilbogget Park, Cabinteely, Dublin		<b>PROBE NO.</b> DP01
<b>CO-ORDINATES</b> 724,205.00 E 724,807.00 N		<b>SHEET</b> Sheet 1 of 1
<b>GROUND LEVEL (mOD)</b>	<b>HAMMER MASS (kg)</b> 50	<b>DATE DRILLED</b> 17/01/2019
<b>CLIENT</b> Dun Laughaire Rathdown Co. Co.	<b>INCREMENT SIZE (mm)</b> 100	<b>PROBE TYPE</b> DPH
<b>ENGINEER</b> DOB	<b>FALL HEIGHT (mm)</b> 500	

Depth (m)	Geotechnical Description	Legend	Depth (m)	Elevation (mOD)	Water	Depth (m)	Probe Readings (Blows/Increment)	Graphic Probe Record
0.0						0.00	2	
						0.10	4	
						0.20	4	
						0.30	3	
						0.40	4	
						0.50	3	
						0.60	2	
						0.70	6	
						0.80	3	
						0.90	3	
						1.00	4	
						1.10	4	
						1.20	4	
						1.30	4	
						1.40	7	
						1.50	6	
						1.60	9	
						1.70	5	
						1.80	5	
						1.90	3	
						2.00	4	
						2.10	3	
						2.20	3	
						2.30	4	
						2.40	3	
						2.50	1	
						2.60	3	
						2.70	3	
						2.80	2	
						2.90	4	
						3.00	3	
						3.10	5	
						3.20	5	
						3.30	6	
						3.40	7	
						3.50	7	
						3.60	14	
						3.70	17	
4.0	End of Probe at 3.80 m							

**GROUNDWATER OBSERVATIONS**

**REMARKS**

IGSL DP LOG 100MM INCREMENTS 21490.GPJ IGSL.GDT 21/1/19



# DYNAMIC PROBE RECORD

REPORT NUMBER

21490

CONTRACT Kilbogget Park, Cabinteely, Dublin

PROBE NO. **DP02**

CO-ORDINATES 724,165.00 E  
724,908.00 N

SHEET Sheet 1 of 1

GROUND LEVEL (mOD)

HAMMER MASS (kg) 50

DATE DRILLED 17/01/2019

CLIENT Dun Laughaire Rathdown Co. Co.

INCREMENT SIZE (mm) 100

ENGINEER DOB

FALL HEIGHT (mm) 500

PROBE TYPE DPH

Depth (m)	Geotechnical Description	Legend	Depth (m)	Elevation (mOD)	Water	Depth (m)	Probe Readings (Blows/Increment)	Graphic Probe Record
0.0						0.00	2	
						0.10	5	
						0.20	8	
						0.30	8	
						0.40	9	
						0.50	5	
						0.60	3	
						0.70	2	
						0.80	3	
						0.90	4	
1.0						1.00	3	
						1.10	3	
						1.20	3	
						1.30	3	
						1.40	3	
						1.50	2	
						1.60	4	
						1.70	4	
						1.80	4	
2.0						1.90	6	
						2.00	5	
						2.10	4	
						2.20	5	
						2.30	5	
						2.40	6	
						2.50	13	
						2.60	21	
						2.70	6	
						2.80	6	
3.0						2.90	10	
						3.00	14	
						3.10	13	
						3.20	16	
						3.30	10	
						3.40	18	
						3.50	23	
						3.60	25	
4.0	End of Probe at 3.70 m							

**GROUNDWATER OBSERVATIONS**

**REMARKS**

IGSL-DP-LOG-100MM-INCREMENTS-21490-GP-IGSL-GDT-21/1/19



# DYNAMIC PROBE RECORD

REPORT NUMBER

21490

<b>CONTRACT</b> Kilbogget Park, Cabinteely, Dublin				<b>PROBE NO.</b> DP03	
<b>CO-ORDINATES</b> 724,108.00 E 724,864.00 N				<b>SHEET</b> Sheet 1 of 1	
<b>GROUND LEVEL (mOD)</b>		<b>HAMMER MASS (kg)</b> 50		<b>DATE DRILLED</b> 17/01/2019	
<b>CLIENT</b> Dun Laughaire Rathdown Co. Co.		<b>INCREMENT SIZE (mm)</b> 100		<b>PROBE TYPE</b> DPH	
<b>ENGINEER</b> DOB		<b>FALL HEIGHT (mm)</b> 500			

Depth (m)	Geotechnical Description	Legend	Depth (m)	Elevation (mOD)	Water	Depth (m)	Probe Readings (Blows/Increment)	Graphic Probe Record
0.0						0.00	3	
0.10						0.10	3	
0.20						0.20	5	
0.30						0.30	6	
0.40						0.40	12	
0.50						0.50	11	
0.60						0.60	16	
0.70						0.70	19	
0.80						0.80	12	
0.90						0.90	7	
1.00						1.00	4	
1.10						1.10	4	
1.20						1.20	3	
1.30						1.30	4	
1.40						1.40	6	
1.50						1.50	3	
1.60						1.60	8	
1.70						1.70	5	
1.80						1.80	3	
1.90						1.90	4	
2.00						2.00	4	
2.10						2.10	4	
2.20						2.20	5	
2.30						2.30	5	
2.40						2.40	4	
2.50						2.50	5	
2.60						2.60	17	
2.70						2.70	22	
2.80						2.80	25	
3.0	End of Probe at 2.90 m							
4.0								

**GROUNDWATER OBSERVATIONS**

**REMARKS**

IGSL DP LOG 100MM INCREMENTS 21490.GPJ IGSL.GDT 21/1/19



# DYNAMIC PROBE RECORD

REPORT NUMBER

21490

CONTRACT Kilbogget Park, Cabinteely, Dublin		PROBE NO. DP04
CO-ORDINATES 724,135.00 E 724,819.00 N		SHEET Sheet 1 of 1
GROUND LEVEL (mOD)	HAMMER MASS (kg) 50	DATE DRILLED 17/01/2019
CLIENT Dun Laughaire Rathdown Co. Co.	INCREMENT SIZE (mm) 100	PROBE TYPE DPH
ENGINEER DOB	FALL HEIGHT (mm) 500	

Depth (m)	Geotechnical Description	Legend	Depth (m)	Elevation (mOD)	Water	Depth (m)	Probe Readings (Blows/Increment)	Graphic Probe Record
0.0						0.00	2	
						0.10	5	
						0.20	9	
						0.30	7	
						0.40	5	
						0.50	15	
						0.60	13	
						0.70	8	
						0.80	6	
						0.90	5	
						1.00	5	
						1.10	2	
						1.20	2	
						1.30	1	
						1.40	1	
						1.50	2	
						1.60	2	
						1.70	2	
						1.80	2	
						1.90	2	
2.0						2.00	3	
						2.10	5	
						2.20	6	
						2.30	7	
						2.40	6	
						2.50	3	
						2.60	1	
						2.70	2	
						2.80	3	
						2.90	2	
3.0						3.00	1	
						3.10	1	
						3.20	1	
						3.30	1	
						3.40	1	
						3.50	2	
						3.60	10	
						3.70	14	
						3.80	21	
4.0	End of Probe at 4.00 m					3.90	25	

**GROUNDWATER OBSERVATIONS**

**REMARKS**

IGSL DP LOG 100MM INCREMENTS 21490.GPJ IGSLGDT 21/1/19

## **IV CBR by Plate Test**





PLATE TEST REPORT SHEET (F3.1)	Applied Pressure/Settlement Curve																								
<p>Reference No. R97889</p> <p>Contract Cabinteely</p> <p>Test No. CBRO1 Reload</p> <p>Location See TP01</p> <p>Depth 0.50mbgl</p> <p>Client DOB</p> <p>Plate Diameter: 450 mm</p> <p>Test Method BS 1377: Part 9: 1990 Test4 - Incremental Loading Test</p> <p>Technician L. Daniels</p> <p>Authorised by </p> <p>Date 16/01/2019</p>	<div style="display: flex; justify-content: space-around; align-items: center;"> </div> <p>Description of soil under test (natural soil, placed fill, sub-base) Brown slightly gravelly CLAY (MADE GROUND)</p> <p>Sample Ref No. .... m bgl</p> <p>Depth .....</p>																								
 <p>The graph plots Settlement (mm) on the y-axis (0.00 to -3.00) against Pressure / Settlement (kN/m<sup>2</sup>) on the x-axis (0 to 120). A dashed line represents the initial loading curve, and a solid line represents the unloading curve. The unloading curve shows a permanent settlement of approximately 1.25 mm at 1.25 kN/m<sup>2</sup>.</p> <table border="1" style="margin: 10px auto;"> <caption>Approximate Data Points from Graph</caption> <thead> <tr> <th>Pressure / Settlement (kN/m<sup>2</sup>)</th> <th>Settlement (mm)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.00</td></tr> <tr><td>1.25</td><td>-0.25</td></tr> <tr><td>2.50</td><td>-0.50</td></tr> <tr><td>4.00</td><td>-0.75</td></tr> <tr><td>6.00</td><td>-1.00</td></tr> <tr><td>8.00</td><td>-1.25</td></tr> <tr><td>10.00</td><td>-1.50</td></tr> <tr><td>12.00</td><td>-1.75</td></tr> <tr><td>15.00</td><td>-2.00</td></tr> <tr><td>20.00</td><td>-2.25</td></tr> <tr><td>25.00</td><td>-2.50</td></tr> </tbody> </table>		Pressure / Settlement (kN/m <sup>2</sup> )	Settlement (mm)	0.00	0.00	1.25	-0.25	2.50	-0.50	4.00	-0.75	6.00	-1.00	8.00	-1.25	10.00	-1.50	12.00	-1.75	15.00	-2.00	20.00	-2.25	25.00	-2.50
Pressure / Settlement (kN/m <sup>2</sup> )	Settlement (mm)																								
0.00	0.00																								
1.25	-0.25																								
2.50	-0.50																								
4.00	-0.75																								
6.00	-1.00																								
8.00	-1.25																								
10.00	-1.50																								
12.00	-1.75																								
15.00	-2.00																								
20.00	-2.25																								
25.00	-2.50																								
<p>Gradient at 1.25 mm settlement intersection = 41</p> <p>Modulus of subgrade reaction = 26 MPa/m</p> <p>(Correction factor applied = 0.64 as per HD 25-26/10)</p> <p style="text-align: right;">Equivalent CBR value in accordance with NRA HD25-26/10 <span style="float: right;">2.7 %</span></p>																									







PLATE TEST REPORT SHEET (F3.1)		Applied Pressure/Settlement Curve																			
Reference No. R97890 Contract Cabinteely Test No. CBR02 Load Location See TP02 Depth 0.40mbgl Client DOB Plate Diameter: 450 mm Test Method BS 1377: Part 9: 1990 Test4 - Incremental Loading Test Technician L. Daniels Authorised by Date 16/01/2019	Description of soil under test (natural soil, placed fill, sub-base) Brown slightly gravelly CLAY (MADE GROUND)	Sample Ref No. Depth ..... m bgl	 																		
 <table border="1" style="margin: 10px auto; border-collapse: collapse;"> <caption>Approximate data points from the Applied Pressure/Settlement Curve</caption> <thead> <tr> <th>Pressure (kN/m<sup>2</sup>)</th> <th>Settlement (mm)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.00</td></tr> <tr><td>2.50</td><td>-0.50</td></tr> <tr><td>4.50</td><td>-1.00</td></tr> <tr><td>6.50</td><td>-1.50</td></tr> <tr><td>8.50</td><td>-2.00</td></tr> <tr><td>10.50</td><td>-2.50</td></tr> <tr><td>12.50</td><td>-3.00</td></tr> <tr><td>14.50</td><td>-3.50</td></tr> </tbody> </table>				Pressure (kN/m <sup>2</sup> )	Settlement (mm)	0.00	0.00	2.50	-0.50	4.50	-1.00	6.50	-1.50	8.50	-2.00	10.50	-2.50	12.50	-3.00	14.50	-3.50
Pressure (kN/m <sup>2</sup> )	Settlement (mm)																				
0.00	0.00																				
2.50	-0.50																				
4.50	-1.00																				
6.50	-1.50																				
8.50	-2.00																				
10.50	-2.50																				
12.50	-3.00																				
14.50	-3.50																				
Gradient at 1.25 mm settlement intersection = 42 Modulus of subgrade reaction = 27 MPa/m Correction factor applied = 0.64 as per HD 25-26/10																					
Equivalent CBR value in accordance with NRA HD25-26/10 <span style="float: right;">2.9 %</span>																					

PLATE TEST REPORT SHEET (F3.1)		Applied Pressure/Settlement Curve	
Reference No. R97890	Contract Cabinteely	Description of soil under test (natural soil, placed fill, sub-base) Brown slightly gravelly CLAY (MADE GROUND)	Sample Ref No. ..... m bgl
Test No. CBR02 Reload	Location See TP02		
Depth 0.40mbgl	Client DOB		
Plate Diameter: 450 mm	Test Method BS 1377: Part 9: 1990 Test4 - Incremental Loading Test		
Technician L. Daniels	Authorised by <i>[Signature]</i>		
Date 16/01/2019			

Pressure / Settlement



Pressure (kN/m2)

Gradient at 1.25 mm settlement intersection = 78 Modulus of subgrade reaction = 50 MPa/m Correction factor applied = 0.64 as per HD 25-26/10	Equivalent CBR value in accordance with NRA HD25-26/10 <b>8.5 %</b>
--	--







PLATE TEST REPORT SHEET (F3.1)		Applied Pressure/Settlement Curve															
Reference No. R97891 Contract Cabinteely Test No. CBR03 Load Location See TPO3 Depth 0.40mbgl Client DOB Plate Diameter: 450 mm Test Method BS 1377: Part 9: 1990 Test4 - Incremental Loading Test Technician L. Daniels Authorised by Date 16/01/2019	Description of soil under test (natural soil, placed fill, sub-base) Brown slightly gravelly CLAY (MADE GROUND)	Sample Ref No. .... m bgl Depth .....	 														
 <table border="1" style="margin: 10px auto; border-collapse: collapse;"> <caption>Graph Data Points (Approximate)</caption> <thead> <tr> <th>Pressure (kN/m<sup>2</sup>)</th> <th>Settlement (mm)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.00</td></tr> <tr><td>21.00</td><td>-0.50</td></tr> <tr><td>45.00</td><td>-1.20</td></tr> <tr><td>70.00</td><td>-1.80</td></tr> <tr><td>100.00</td><td>-2.50</td></tr> <tr><td>125.00</td><td>-3.00</td></tr> </tbody> </table>				Pressure (kN/m <sup>2</sup> )	Settlement (mm)	0.00	0.00	21.00	-0.50	45.00	-1.20	70.00	-1.80	100.00	-2.50	125.00	-3.00
Pressure (kN/m <sup>2</sup> )	Settlement (mm)																
0.00	0.00																
21.00	-0.50																
45.00	-1.20																
70.00	-1.80																
100.00	-2.50																
125.00	-3.00																
Gradient at 1.25 mm settlement intersection = 33 Modulus of subgrade reaction = 21 MPa/m Correction factor applied = 0.64 as per HD 25-26/10																	
Equivalent CBR value in accordance with NRA HD25-26/10 <span style="float: right;">1.9 %</span>																	

PLATE TEST REPORT SHEET (F3.1)		Applied Pressure/Settlement Curve																			
Reference No. R97891	Contract Cabinteely	Description of soil under test (natural soil, placed fill, sub-base) Brown slightly gravelly CLAY (MADE GROUND)	Sample Ref No. ..... m bgl																		
Test No. CBR03 Reload	Location See TPO3																				
Depth 0.40mbgl	Client DOB																				
Plate Diameter: 450 mm	Test Method BS 1377: Part 9: 1990 Test4 - Incremental Loading Test																				
Technician L. Daniels	Authorised by .....																				
Date 16/01/2019																					
		 																			
 <table border="1"> <caption>Data points from the Applied Pressure/Settlement Curve</caption> <thead> <tr> <th>Pressure (kN/m<sup>2</sup>)</th> <th>Settlement (mm)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.00</td></tr> <tr><td>15.00</td><td>-0.20</td></tr> <tr><td>25.00</td><td>-0.40</td></tr> <tr><td>45.00</td><td>-0.75</td></tr> <tr><td>65.00</td><td>-1.00</td></tr> <tr><td>80.00</td><td>-1.15</td></tr> <tr><td>90.00</td><td>-1.30</td></tr> <tr><td>115.00</td><td>-1.65</td></tr> </tbody> </table>				Pressure (kN/m <sup>2</sup> )	Settlement (mm)	0.00	0.00	15.00	-0.20	25.00	-0.40	45.00	-0.75	65.00	-1.00	80.00	-1.15	90.00	-1.30	115.00	-1.65
Pressure (kN/m <sup>2</sup> )	Settlement (mm)																				
0.00	0.00																				
15.00	-0.20																				
25.00	-0.40																				
45.00	-0.75																				
65.00	-1.00																				
80.00	-1.15																				
90.00	-1.30																				
115.00	-1.65																				
Gradient at 1.25 mm settlement intersection = 64 Modulus of subgrade reaction = 41 MPa/m Correction factor applied = 0.64 as per HD 25-26/10		Equivalent CBR value in accordance with NRA HD25-26/10 6.1 %																			


**PLATE TEST REPORT SHEET (F3.1)**

**Applied Pressure/Settlement Curve**

Reference No. R97892  
 Contract Cabinteely  
 Test No. CBR04 Load  
 Location See TP04  
 Depth 0.40mbgl  
 Client DOB  
 Plate Diameter: 450 mm  
 Test Method BS 1377: Part 9: 1990 Test4 - Incremental Loading Test  
 Technician L. Daniels  
 Authorised by  
 Date 16/01/2019

Description of soil under test  
 (natural soil, placed fill, sub-base)  
 Brown slightly gravelly CLAY (MADE GROUND)

Sample Ref No. .... m bgl  
 Depth .....



Gradient at 1.25 mm settlement intersection = 27  
 Modulus of subgrade reaction = 18 MPa/m  
 Correction factor applied = 0.64 as per HD 25-26/10

Equivalent CBR value in accordance with NRA HD25-26/10

1.4 %


**PLATE TEST REPORT SHEET (F3.1)**

**Applied Pressure/Settlement Curve**

Reference No. R97892  
 Contract Cabinteely  
 Test No. CBR04 Rebad  
 Location See TP04  
 Depth 0.40mbgl  
 Client DOB  
 Plate Diameter: 450 mm  
 Test Method BS 1377: Part 9: 1990 Test4 - Incremental Loading Test  
 Technician L. Daniels  
 Authorised by  
 Date 16/01/2019

Description of soil under test  
 (natural soil, placed fill, sub-base)  
 Brown slightly gravelly CLAY (MADE GROUND)

Sample Ref No. .... m bgl  
 Depth .....



Gradient at 1.25 mm settlement intersection = 53  
 Modulus of subgrade reaction = 34 MPa/m  
 Correction factor applied = 0.64 as per HD 25-26/10

Equivalent CBR value in accordance with NRA HD25-26/10

4.3 %

## **Appendix V BRE Digest 365**







## **Appendix VI Laboratory**

### **a. Geotechnical**



# TEST REPORT


## Determination of Particle Size Distribution

Tested in accordance with: BS1377:Part 2:1990, clause 9.2 & 9.5  
(note: Sedimentation stage not accredited)



particle size	% passing	Contract No: 21490	Report No. R98216
75	100	Contract: Kilbogget Park, Cabinteely, Co.Dublin	
63	100	BH/TP: TP01	
50	100	Sample No. AA110727	Lab. Sample No. A19/0259
37.5	89	Sample Type: B	
28	85	Depth (m) 1.00	Customer: Donnachadh O'Brien & Associates, Unit 5C, Elm House, Millennium Park, Naas Co. Kildare.
20	83	Date Received 23/01/2019	Date Testing started 25/01/2019
14	80	Description: Brown slightly sandy, gravelly, CLAY	
10	77		
6.3	73		
5	71		
3.35	66		
2	59		
1.18	53		
0.6	46		
0.425	43		
0.3	39		
0.15	33		
0.063	25		
0.040	21		
0.028	20		
0.018	17		
0.011	15		
0.007	13		
0.005	11		
0.002	7		

Remarks: Note: Clauses 9.2 and Clause 9.5 of BS1377 Part 2:1990 have been superseded by ISO17891-4:2016. Sample size did not meet the requirements of BS1377






# TEST REPORT

## Determination of Particle Size Distribution

Tested in accordance with: BS1377:Part2:1990, clause 9.2 & 9.5  
(note: Sedimentation stage not accredited)



Contract No:	21490	Report No.	R98217
Contract:	Kilbogget Park, Cabinteely, Co.Dublin		
BH/TP:	TP04		
Sample No.	AA110725	Lab. Sample No.	A19/0264
Sample Type:	B		
Depth (m)	2.00	Customer:	Donnachadh O'Brien & Associates, Unit 5C, Elm House, Millennium Park, Naas Co. Kildare.
Date Received	23/01/2019	Date Testing started	25/01/2019
Description:	Brown slightly sandy, gravelly, SILT		
Remarks	Note: Clause 9.2 and Clause 9.5 of BS1377:Part 2:1990 have been superseded by ISO17892-4:2016		



## **Appendix VI Laboratory**

### **b. Chemical and Environmental**



# Final Report

---

**Report No.:** 19-03882-1

**Initial Date of Issue:** 18-Feb-2019

**Client:** IGSL

**Client Address:** M7 Business Park  
Naas  
County Kildare  
Ireland

**Contact(s):** Darren Keogh

**Project:** 21490 Kilbogget Park, Cabinteely


**Quotation No.:** **Date Received:** 04-Feb-2019

**Order No.:** **Date Instructed:** 04-Feb-2019

**No. of Samples:** 6

**Turnaround (Wkdays):** 7 **Results Due:** 12-Feb-2019

**Date Approved:** 18-Feb-2019

**Approved By:**  


**Details:** Glynn Harvey, Laboratory Manager

---

**Project: 21490 Kilbogget Park, Cabinteely**

Client: IGSL	Chemtest Job No.:	19-03882	19-03882	19-03882	19-03882
Quotation No.:	Chemtest Sample ID.:	766414	766415	766417	766418
	Sample Location:	TP1	TP2	TP3	TP4
	Sample Type:	SOIL	SOIL	SOIL	SOIL
	Top Depth (m):	0.50	1.00	2.00	1.00
Determinand	Accred.	SOP	Units	LOD	
Ammonium	U	1220	mg/l	0.050	0.089
Ammonium	N	1220	mg/kg	0.10	0.89
Boron (Dissolved)	U	1450	µg/l	20	< 20
Boron (Dissolved)	U	1450	mg/kg	0.20	< 0.20
					0.071
					4.2
					42
					< 20
					< 0.20
					< 0.20
					< 0.20

Determinand	Accred.	SOP	Chemtest Job No.:		Sample Location:	LOD	19-03882		19-03882	19-03882	19-03882	19-03882	19-03882
			Chemtest Sample ID.:	766414			766415	766416					
ACM Type	U	2192	TP1	TP2	TP2	TP2	TP2	TP2	TP3	TP4	TP4	TP4	
Asbestos Identification	U	2192	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	SOIL	
ACM Detection Stage	U	2192	0.50	1.00	1.00	1.00	1.00	1.00	2.00	1.00	1.00	2.00	
Moisture	N	2030	COVENTRY	COVENTRY	COVENTRY	COVENTRY	COVENTRY	COVENTRY	COVENTRY	COVENTRY	COVENTRY	COVENTRY	
pH	U	2010	No Asbestos Detected	No Asbestos Detected	No Asbestos Detected	No Asbestos Detected	No Asbestos Detected	No Asbestos Detected	No Asbestos Detected	No Asbestos Detected	No Asbestos Detected	No Asbestos Detected	
Boron (Hot Water Soluble)	U	2120	16	12	19	19	16	16	16	16	16	21	
Sulphate (2:1 Water Soluble) as SO4	U	2120	< 0.40	0.86	[A] 8.3	[A] 8.3	< 0.40	< 0.40	< 0.40	< 0.40	< 0.40	[A] 7.9	
Sulphur (Elemental)	U	2180	0.010		< 0.010	< 0.010						< 0.010	
Cyanide (Total)	U	2300	1.0	[A] 3.9	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] 8.8	[A] 1.4	[A] 1.4		
Sulphide (Easily Liberatable)	N	2325	0.50	[A] < 0.50	[A] < 0.50	[A] < 0.50	[A] < 0.50	[A] < 0.50	[A] < 0.50	[A] < 0.50	[A] < 0.50		
Sulphate (Acid Soluble)	U	2430	0.50	[A] 1.8	[A] 2.1	[A] 2.1	[A] 2.1	[A] 2.1	[A] 23	[A] 6.8	[A] 6.8		
Arsenic	U	2450	0.010	[A] 0.066	[A] 0.024	[A] 0.024	[A] 0.024	[A] 0.024	[A] 0.027	[A] 0.050	[A] 0.050		
Barium	U	2450	1.0	35	17	17	17	17	21	31	31		
Cadmium	U	2450	10	260	47	47	47	47	72	170	170		
Chromium	U	2450	0.10	2.7	0.62	0.62	0.62	0.62	1.2	1.8	1.8		
Molybdenum	U	2450	1.0	35	17	17	17	17	16	23	23		
Antimony	N	2450	2.0	36	< 2.0	< 2.0	< 2.0	< 2.0	2.1	22	22		
Copper	U	2450	0.50	5.8	2.4	2.4	2.4	2.4	2.3	3.5	3.5		
Mercury	U	2450	0.50	77	16	16	16	16	21	53	53		
Nickel	U	2450	0.10	0.42	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10	0.28	0.28		
Lead	U	2450	0.50	63	24	24	24	24	30	37	37		
Selenium	U	2450	0.20	190	25	25	25	25	32	130	130		
Zinc	U	2450	0.50	380	< 0.20	< 0.20	< 0.20	< 0.20	< 0.20	< 0.20	< 0.20		
Chromium (Trivalent)	N	2490	0.50	35	17	17	17	17	16	23	23		
Chromium (Hexavalent)	N	2490	0.50	< 0.50	< 0.50	< 0.50	< 0.50	< 0.50	< 0.50	< 0.50	< 0.50		
Total Organic Carbon	U	2625	0.20	[A] 3.0	[A] 2.9	[A] 2.9	[A] 2.9	[A] 2.9	[A] 0.52	[A] 0.79	[A] 0.79		
Mineral Oil	N	2670	10	32	< 10	< 10	< 10	< 10	31	10	10		
Aliphatic TPH >C5-C6	N	2680	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		
Aliphatic TPH >C6-C8	N	2680	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		
Aliphatic TPH >C8-C10	U	2680	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		
Aliphatic TPH >C10-C12	U	2680	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		
Aliphatic TPH >C12-C16	U	2680	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		
Aliphatic TPH >C16-C21	U	2680	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		
Aliphatic TPH >C21-C35	U	2680	1.0	[A] 32	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] 31	[A] 9.9	[A] 9.9		
Aliphatic TPH >C35-C44	N	2680	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		
Total Aliphatic Hydrocarbons	N	2680	5.0	[A] 32	[A] < 5.0	[A] < 5.0	[A] < 5.0	[A] < 5.0	[A] 31	[A] 9.9	[A] 9.9		
Aromatic TPH >C5-C7	N	2680	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		
Aromatic TPH >C7-C8	N	2680	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		
Aromatic TPH >C8-C10	U	2680	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0		

**Results - Soil**

Client: IGSL	Chemtest Job No.:		19-03882		19-03882		19-03882		19-03882		19-03882	
	Quotation No.:	Chemtest Sample ID.:	766414	766415	766416	766417	766418	766419	766419	766419	766419	766419
Determindand	Accred.	SOP	Units	LOD	Sample Location:		Sample Type:		Top Depth (m):		Asbestos Lab:	
					TP1	TP2	TP3	TP4	TP1	TP2	TP3	TP4
Aromatic TPH >C10-C12	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0
Aromatic TPH >C12-C16	U	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0
Aromatic TPH >C16-C21	U	2680	mg/kg	1.0	[A] 1.5	[A] < 1.0	[A] < 1.0	[A] 5.0	[A] 4.1	[A] 5.0	[A] 4.1	[A] 4.1
Aromatic TPH >C21-C35	U	2680	mg/kg	1.0	[A] 72	[A] < 1.0	[A] < 1.0	[A] 56	[A] 240	[A] 56	[A] 240	[A] 240
Aromatic TPH >C35-C44	N	2680	mg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0
Total Aromatic Hydrocarbons	N	2680	mg/kg	5.0	[A] 74	[A] < 5.0	[A] < 5.0	[A] 61	[A] 300	[A] 61	[A] 300	[A] 300
Total Petroleum Hydrocarbons	N	2680	mg/kg	10.0	[A] 110	[A] < 10	[A] < 10	[A] 93	[A] 310	[A] 93	[A] 310	[A] 310
Benzene	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0
Toluene	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0
Ethylbenzene	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0
m & p-Xylene	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0
o-Xylene	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0
Methyl Tert-Butyl Ether	U	2760	µg/kg	1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0	[A] < 1.0
Naphthalene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	0.55	< 0.10	0.55	< 0.10	< 0.10
Acenaphthylene	N	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	0.46	< 0.10	0.46	< 0.10	< 0.10
Acenaphthene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	1.2	< 0.10	1.2	< 0.10	< 0.10
Fluorene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	1.1	< 0.10	1.1	< 0.10	< 0.10
Phenanthrene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	3.9	0.28	3.9	0.28	0.28
Anthracene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	0.92	< 0.10	0.92	< 0.10	< 0.10
Fluoranthene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	4.5	0.51	4.5	0.51	0.51
Pyrene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	3.9	0.60	3.9	0.60	0.60
Benzo[a]anthracene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	2.0	< 0.10	2.0	< 0.10	< 0.10
Chrysene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	2.2	< 0.10	2.2	< 0.10	< 0.10
Benzo[b]fluoranthene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	3.0	< 0.10	3.0	< 0.10	< 0.10
Benzo[k]fluoranthene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	1.0	< 0.10	1.0	< 0.10	< 0.10
Benzo[a]pyrene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	2.2	< 0.10	2.2	< 0.10	< 0.10
Indeno(1,2,3-c,d)Pyrene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	1.0	< 0.10	1.0	< 0.10	< 0.10
Dibenz(a,h)Anthracene	N	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10
Benzo[g,h,i]perylene	U	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	1.1	< 0.10	1.1	< 0.10	< 0.10
Coronene	N	2800	mg/kg	0.10	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10	< 0.10
Total Of 17 PAH's	N	2800	mg/kg	2.0	< 2.0	< 2.0	< 2.0	29	< 2.0	29	< 2.0	< 2.0
PCB 28	U	2815	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010
PCB 52	U	2815	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010
PCB 90+101	U	2815	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010
PCB 118	U	2815	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010
PCB 153	U	2815	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010
PCB 138	U	2815	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010
PCB 180	U	2815	mg/kg	0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010	[A] < 0.010
Total PCBs (7 Congeners)	N	2815	mg/kg	0.10	[A] < 0.10	[A] < 0.10	[A] < 0.10	[A] < 0.10	[A] < 0.10	[A] < 0.10	[A] < 0.10	[A] < 0.10
Total Phenols	U	2920	mg/kg	0.30	< 0.30	< 0.30	< 0.30	< 0.30	< 0.30	< 0.30	< 0.30	< 0.30

## Results - Single Stage WAC

Project: 21490 Kilbogget Park, Cabinteely  
 Chemtest Job No: 19-03882  
 Chemtest Sample ID: 766414

Sample Ref:  
 Sample ID: TP1  
 Sample Location: 0.50  
 Top Depth(m):  
 Bottom Depth(m):  
 Sampling Date:

Determindand	SOP	Accred.	Units		Landfill Waste Acceptance Criteria
Total Organic Carbon	2625	U	[A] 3.0		Inert Waste Landfill
Loss On Ignition	2610	U	31		Stable, Non-reactive hazardous waste in non-hazardous Landfill
Total BTEX	2760	U	[A] < 0.010		Hazardous Waste Landfill
Total PCBs (7 Congeners)	2815	U	< 0.10		
TPH Total WAC (Mineral Oil)	2670	U	[A] 110		
Total (Of 17) PAH's	2800	N	< 2.0		
pH	2010	U	8.2		
Acid Neutralisation Capacity	2015	N	0.11		To evaluate
<b>Eluate Analysis</b>			<b>10:1 Eluate mg/kg</b>		<b>Limit values for compliance leaching test using BS EN 12457 at L/S 10 l/kg</b>
Arsenic	1450	U	< 0.0010	< 0.050	0.5
Barium	1450	U	0.0032	< 0.50	20
Cadmium	1450	U	< 0.00010	< 0.010	0.04
Chromium	1450	U	< 0.0010	< 0.050	0.5
Copper	1450	U	< 0.0010	< 0.050	2
Mercury	1450	U	< 0.00050	< 0.0050	0.01
Molybdenum	1450	U	0.0052	0.052	0.5
Nickel	1450	U	< 0.0010	< 0.050	0.4
Lead	1450	U	< 0.0010	< 0.010	0.5
Antimony	1450	U	< 0.0010	< 0.010	0.06
Selenium	1450	U	< 0.0010	< 0.010	0.1
Zinc	1450	U	< 0.0010	< 0.50	4
Chloride	1220	U	< 1.0	< 10	800
Fluoride	1220	U	0.11	1.1	10
Sulphate	1220	U	< 1.0	< 10	1000
Total Dissolved Solids	1020	N	35	350	4000
Phenol Index	1920	U	< 0.030	< 0.30	1
Dissolved Organic Carbon	1610	U	7.2	72	500

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	16

### Waste Acceptance Criteria

Landfill WAC analysis (specifically leaching test results) must not be used for hazardous waste classification purposes. This analysis is only applicable for hazardous waste landfill acceptance and does not give any indication as to whether a waste may be hazardous or non-hazardous.

## Results - Single Stage WAC

Project: 21490 Kilboogget Park, Cabinteely  
 Chemtest Job No: 19-03882  
 Chemtest Sample ID: 766415

Sample Ref: TP2  
 Sample ID: 1.00  
 Sample Location:  
 Top Depth(m):  
 Bottom Depth(m):  
 Sampling Date:

Determinand	SOP	Accred.	Units		Landfill Waste Acceptance Criteria			
			10:1 Eluate mg/l	%	Inert Waste Landfill	Stable, Non-reactive hazardous waste in non-hazardous Landfill	Hazardous Waste Landfill	
Total Organic Carbon	2625	U		%	[A] 2.9	3	5	6
Loss On Ignition	2610	U		%	2.5	--	--	10
Total BTEX	2760	U		mg/kg	[A] < 0.010	6	--	--
Total PCBs (7 Congeners)	2815	U		mg/kg	< 0.10	1	--	--
TPH Total WAC (Mineral Oil)	2670	U		mg/kg	[A] < 10	500	--	--
Total (Of 17) PAH's	2800	N		mg/kg	< 2.0	100	--	--
pH	2010	U			8.5	--	>6	--
Acid Neutralisation Capacity	2015	N		mol/kg	0.018	--	To evaluate	To evaluate
<b>Eluate Analysis</b>					<b>10:1 Eluate mg/kg</b>	<b>Limit values for compliance leaching test using BS EN 12457 at L/S 10 l/kg</b>		
Arsenic	1450	U		< 0.0010	< 0.050	0.5	2	25
Barium	1450	U		0.0012	< 0.50	20	100	300
Cadmium	1450	U		< 0.00010	< 0.010	0.04	1	5
Chromium	1450	U		< 0.0010	< 0.050	0.5	10	70
Copper	1450	U		< 0.0010	< 0.050	2	50	100
Mercury	1450	U		< 0.00050	< 0.0050	0.01	0.2	2
Molybdenum	1450	U		< 0.0010	< 0.050	0.5	10	30
Nickel	1450	U		< 0.0010	< 0.050	0.4	10	40
Lead	1450	U		< 0.0010	< 0.010	0.5	10	50
Antimony	1450	U		< 0.0010	< 0.010	0.06	0.7	5
Selenium	1450	U		< 0.0010	< 0.010	0.1	0.5	7
Zinc	1450	U		< 0.0010	< 0.50	4	50	200
Chloride	1220	U		< 1.0	< 10	800	15000	25000
Fluoride	1220	U		0.14	1.4	10	150	500
Sulphate	1220	U		< 1.0	< 10	1000	20000	50000
Total Dissolved Solids	1020	N		38	380	4000	60000	100000
Phenol Index	1920	U		< 0.030	< 0.30	1	--	--
Dissolved Organic Carbon	1610	U		6.5	65	500	800	1000

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	12

### Waste Acceptance Criteria

Landfill WAC analysis (specifically leaching test results) must not be used for hazardous waste classification purposes. This analysis is only applicable for hazardous waste landfill acceptance and does not give any indication as to whether a waste may be hazardous or non-hazardous.

## Results - Single Stage WAC

Project: 21490 Kilbosquet Park, Cabinteely  
 Chemtest Job No: 19-03882  
 Chemtest Sample ID: 766417

Sample Ref:  
 Sample ID: TP3  
 Sample Location: 2.00  
 Top Depth(m):  
 Bottom Depth(m):  
 Sampling Date:

Determinand	SOP	Accred.	Units		Landfill Waste Acceptance Criteria Limits		
				%	Inert Waste Landfill	Stable, Non-reactive hazardous waste in non-hazardous Landfill	Hazardous Waste Landfill
Total Organic Carbon	2625	U		[A] 0.52	3	5	6
Loss On Ignition	2610	U		2.9	--	--	10
Total BTEX	2760	U		[A] <0.010	6	--	--
Total PCBs (7 Congeners)	2815	U		<0.10	1	--	--
TPH Total WAC (Mineral Oil)	2670	U		[A] 93	500	--	--
Total (Of 17) PAH's	2800	N		29	100	--	--
pH	2010	U		8.5	--	>6	--
Acid Neutralisation Capacity	2015	N		0.022	--	To evaluate	To evaluate
<b>Eluate Analysis</b>				<b>10:1 Eluate mg/kg</b>	<b>Limit values for compliance leaching test using BS EN 12457 at L/S 10 l/kg</b>		
Arsenic	1450	U	10:1 Eluate mg/l	<0.050	0.5	2	25
Barium	1450	U		<0.50	20	100	300
Cadmium	1450	U		<0.0010	0.04	1	5
Chromium	1450	U		<0.050	0.5	10	70
Copper	1450	U		<0.0010	2	50	100
Mercury	1450	U		<0.0050	0.01	0.2	2
Molybdenum	1450	U		<0.050	0.5	10	30
Nickel	1450	U		<0.050	0.4	10	40
Lead	1450	U		<0.010	0.5	10	50
Antimony	1450	U		<0.010	0.06	0.7	5
Selenium	1450	U		<0.010	0.1	0.5	7
Zinc	1450	U		<0.010	4	50	200
Chloride	1220	U		12	800	15000	25000
Fluoride	1220	U		1.0	10	150	500
Sulphate	1220	U		32	1000	20000	50000
Total Dissolved Solids	1020	N		580	4000	60000	100000
Phenol Index	1920	U		<0.30	1	-	-
Dissolved Organic Carbon	1610	U		74	500	800	1000

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	16

### Waste Acceptance Criteria

Landfill WAC analysis (specifically leaching test results) must not be used for hazardous waste classification purposes. This analysis is only applicable for hazardous waste landfill acceptance and does not give any indication as to whether a waste may be hazardous or non-hazardous.

## Results - Single Stage WAC

Project: 21490 Kilbogget Park, Cabinteely  
 Chemtest Job No: 19-03882  
 Chemtest Sample ID: 766418

Sample Ref: TP4  
 Sample Location: 1.00  
 Top Depth(m):  
 Bottom Depth(m):

Determinand	SOP	Accred.	Units		Landfill Waste Acceptance Criteria		
			%	mg/kg	Inert Waste Landfill	Stable, Non-reactive hazardous waste in non-hazardous Landfill	Hazardous Waste Landfill
Total Organic Carbon	2625	U	[A] 0.79		3	5	6
Loss On Ignition	2610	U	6.9		--	--	10
Total BTEX	2760	U	[A] < 0.010		1	--	--
Total PCBs (7 Congeners)	2815	U	< 0.10		1	--	--
TPH Total WAC (Mineral Oil)	2670	U	[A] 310		500	--	--
Total (Of 17) PAH's	2800	N	< 2.0		100	--	--
pH	2010	U	8.2		--	> 6	--
Acid Neutralisation Capacity	2015	N	0.040		--	To evaluate	To evaluate
<b>Eluate Analysis</b>			<b>10:1 Eluate mg/kg</b>		<b>Limit values for compliance leaching test using BS EN 12457 at L/S 10 l/kg</b>		
Arsenic	1450	U	< 0.0010		0.5	2	25
Barium	1450	U	0.0038		20	100	300
Cadmium	1450	U	< 0.00010		0.04	1	5
Chromium	1450	U	< 0.0010		0.5	10	70
Copper	1450	U	< 0.0010		2	50	100
Mercury	1450	U	< 0.00050		0.01	0.2	2
Molybdenum	1450	U	0.0051		0.5	10	30
Nickel	1450	U	< 0.0010		0.4	10	40
Lead	1450	U	< 0.0010		0.5	10	50
Antimony	1450	U	< 0.0010		0.06	0.7	5
Selenium	1450	U	< 0.0010		0.1	0.5	7
Zinc	1450	U	< 0.0010		4	50	200
Chloride	1220	U	1.1		800	15000	25000
Fluoride	1220	U	0.10		10	150	500
Sulphate	1220	U	< 1.0		1000	20000	50000
Total Dissolved Solids	1020	N	42		4000	60000	100000
Phenol Index	1920	U	< 0.030		1	--	--
Dissolved Organic Carbon	1610	U	7.1		500	800	1000

Solid Information	
Dry mass of test portion/kg	0.090
Moisture (%)	16

### Waste Acceptance Criteria

Landfill WAC analysis (specifically leaching test results) must not be used for hazardous waste classification purposes. This analysis is only applicable for hazardous waste landfill acceptance and does not give any indication as to whether a waste may be hazardous or non-hazardous.

## Deviations

In accordance with UKAS Policy on Deviating Samples TPS 63. Chemtest have a procedure to ensure 'upon receipt of each sample a competent laboratory shall assess whether the sample is suitable with regard to the requested test(s)'. This policy and the respective holding times applied, can be supplied upon request. The reason a sample is declared as deviating is detailed below. Where applicable the analysis remains UKAS/MCERTs accredited but the results may be compromised.

Sample:	Sample Ref:	Sample ID:	Sample Location:	Sampled Date:	Deviation Code(s):	Containers Received:
766414			TP1		A	Amber Glass 250ml
766414			TP1		A	Amber Glass 60ml
766415			TP2		A	Amber Glass 250ml
766415			TP2		A	Amber Glass 60ml
766416			TP2		A	Amber Glass 250ml
766417			TP3		A	Amber Glass 250ml
766417			TP3		A	Amber Glass 60ml
766418			TP4		A	Amber Glass 250ml
766418			TP4		A	Amber Glass 60ml
766419			TP4		A	Amber Glass 250ml

SOP	Title	Parameters included	Method summary
1020	Electrical Conductivity and Total Dissolved Solids (TDS) in Waters	Electrical Conductivity and Total Dissolved Solids (TDS) in Waters	Conductivity Meter
1220	Anions, Alkalinity & Ammonium in Waters	Fluoride; Chloride; Nitrite; Nitrate; Total; Oxidisable Nitrogen (TON); Sulfate; Phosphate; Alkalinity; Ammonium	Automated colorimetric analysis using 'Aquakem 600' Discrete Analyser.
1450	Metals in Waters by ICP-MS	Metals, including: Antimony; Arsenic; Barium; Beryllium; Boron; Cadmium; Chromium; Cobalt; Copper; Lead; Manganese; Mercury; Molybdenum; Nickel; Selenium; Tin; Vanadium; Zinc	Filtration of samples followed by direct determination by inductively coupled plasma mass spectrometry (ICP-MS).
1610	Total/Dissolved Organic Carbon in Waters	Organic Carbon	TOC Analyser using Catalytic Oxidation
1920	Phenols in Waters by HPLC	Phenolic compounds including: Phenol, Cresols, Xylenols, Trimethylphenols Note: Chlorophenols are excluded.	Determination by High Performance Liquid Chromatography (HPLC) using electrochemical detection.
2010	pH Value of Soils	pH	pH Meter
2015	Acid Neutralisation Capacity	Acid Reserve	Titration
2030	Moisture and Stone Content of Soils (Requirement of MCERTS)	Moisture content	Determination of moisture content of soil as a percentage of its as received mass obtained at <37°C.
2120	Water Soluble Boron, Sulphate, Magnesium & Chromium	Boron; Sulphate; Magnesium; Chromium	Aqueous extraction / ICP-OES
2180	Sulphur (Elemental) in Soils by HPLC	Sulphur	Dichloromethane extraction / HPLC with UV detection
2192	Asbestos	Asbestos	Polarised light microscopy / Gravimetry
2300	Cyanides & Thiocyanate in Soils	Free (or easy liberatable) Cyanide; total Cyanide; complex Cyanide; Thiocyanate	Alkaline extraction followed by colorimetric determination using Automated Flow Injection Analyser.
2325	Sulphide in Soils	Sulphide	Steam distillation with sulphuric acid / analysis by 'Aquakem 600' Discrete Analyser, using N,N-dimethyl-p-phenylenediamine.
2430	Total Sulphate in soils	Total Sulphate	Acid digestion followed by determination of sulphate in extract by ICP-OES.
2450	Acid Soluble Metals in Soils	Metals, including: Arsenic; Barium; Beryllium; Cadmium; Chromium; Cobalt; Copper; Lead; Manganese; Mercury; Molybdenum; Nickel; Selenium; Vanadium; Zinc	Acid digestion followed by determination of metals in extract by ICP-MS.
2490	Hexavalent Chromium in Soils	Chromium [VI]	Soil extracts are prepared by extracting dried and ground soil samples into boiling water. Chromium [VI] is determined by 'Aquakem 600' Discrete Analyser using 1,5-diphenylcarbazide.
2610	Loss on Ignition	loss on ignition (LOI)	Determination of the proportion by mass that is lost from a soil by ignition at 550°C.
2625	Total Organic Carbon in Soils	Total organic Carbon (TOC)	Determined by high temperature combustion under oxygen, using an Eltra elemental analyser.
2670	Total Petroleum Hydrocarbons (TPH) in Soils by GC-FID	TPH (C6-C40); optional carbon banding, e.g. 3-band - GRO, DRO & LRO*TPH C8-C40	Dichloromethane extraction / GC-FID
2680	TPH A/A Split	Aliphatics: >C5-C6, >C6-C8, >C8-C10, >C10-C12, >C12-C16, >C16-C21, >C21-C35, >C35-C44 Aromatics: >C5-C7, >C7-C8, >C8-C10, >C10-C12, >C12-C16, >C16-C21, >C21-C35, >C35-C44	Dichloromethane extraction / GCxGC FID detection

SOP	Title	Parameters included	Method summary
2760	Volatile Organic Compounds (VOCs) in Soils by Headspace GC-MS	Volatile organic compounds, including BTEX and halogenated Aliphatic/Aromatics.(cf. USEPA Method 8260)*please refer to UKAS schedule	Automated headspace gas chromatographic (GC) analysis of a soil sample, as received, with mass spectrometric (MS) detection of volatile organic compounds.
2800	Speciated Polynuclear Aromatic Hydrocarbons (PAH) in Soil by GC-MS	Acenaphthene*; Acenaphthylene; Anthracene*; Benzo[a]Anthracene*; Benzo[a]Pyrene*; Benzo[b]Fluoranthene*; Benzo[ghi]Perylene*; Benzo[k]Fluoranthene; Chrysene*; Dibenz[ah]Anthracene; Fluoranthene*; Fluorene*; Indeno[123cd]Pyrene*; Naphthalene*; Phenanthrene*; Pyrene*	Dichloromethane extraction / GC-MS
2815	Polychlorinated Biphenyls (PCB) ICES7Congeners in Soils by GC-MS	ICES7 PCB congeners	Acetone/Hexane extraction / GC-MS
2920	Phenols in Soils by HPLC	Phenolic compounds including Resorcinol, Phenol, Methylphenols, Dimethylphenols, 1-Naphthol and TrimethylphenolsNote: chlorophenols are excluded.	60:40 methanol/water mixture extraction, followed by HPLC determination using electrochemical detection.
640	Characterisation of Waste (Leaching)	Waste material including soil, sludges and granular waste	ComplianceTest for Leaching of Granular Waste Material and Sludge

## **Report Information**

### **Key**

---

- U UKAS accredited
- M MCERTS and UKAS accredited
- N Unaccredited
- S This analysis has been subcontracted to a UKAS accredited laboratory that is accredited for this analysis
- SN This analysis has been subcontracted to a UKAS accredited laboratory that is not accredited for this analysis
- T This analysis has been subcontracted to an unaccredited laboratory
- I/S Insufficient Sample
- U/S Unsuitable Sample
- N/E not evaluated
- < "less than"
- > "greater than"

Comments or interpretations are beyond the scope of UKAS accreditation

The results relate only to the items tested

Uncertainty of measurement for the determinands tested are available upon request

None of the results in this report have been recovery corrected

All results are expressed on a dry weight basis

The following tests were analysed on samples as received and the results subsequently corrected to a dry weight basis TPH, BTEX, VOCs, SVOCs, PCBs, Phenols

For all other tests the samples were dried at < 37°C prior to analysis

All Asbestos testing is performed at the indicated laboratory

Issue numbers are sequential starting with 1 all subsequent reports are incremented by 1

### **Sample Deviation Codes**

---

- A - Date of sampling not supplied
- B - Sample age exceeds stability time (sampling to extraction)
- C - Sample not received in appropriate containers
- D - Broken Container
- E - Insufficient Sample (Applies to LOI in Trommel Fines Only)

### **Sample Retention and Disposal**

---

All soil samples will be retained for a period of 45 days from the date of receipt

All water samples will be retained for 14 days from the date of receipt


Charges may apply to extended sample storage

If you require extended retention of samples, please email your requirements to:

[customerservices@chemtest.com](mailto:customerservices@chemtest.com)

## **Appendix VII Site Plan**

# Google Maps Kilbogget Park



Imagery ©2019 DigitalGlobe, Map data ©2019 Google 20 m




## Kilbogget Park

Dublin

4.1 ★★★★★ · 14 reviews

Terrain


 Dublin

### Photos

ON TOP SCALE CONNECTION TO CHECK ALL DIMENSIONS AND REPORT ANY ERRORS TO CLIENT



SCALE 1:500 @ A1 (1:1000 @ A2)



**LEGEND:**

	TRIAL PIT
	DYNAMIC PROBE
	SOUNDING
	PLATE BEARING TEST / CBR TEST
	BRE-306
	INFILTRATION TEST

**NOTES:**

- THIS DRAWING IS TO BE READ IN CONJUNCTION WITH THE SITE INVESTIGATION SPECIFICATION AND DRAWINGS AND OUR LATEST SURVEY AND CADASTRAL DRAWINGS.
- THIS DRAWING IS TO REFER TO THE SITE INVESTIGATION STAGE PRELIMINARY HEALTH AND SAFETY ASSESSMENT RISK ASSESSMENTS.

A ISSUED FOR INFORMATION		07.12.2018	A1	A2	AL
Rev.	Date	Drawn	Checked	Drawn	Checked
<p>UNIT 3C            1500-1505            1506-1507            1508-1509            1510-1511            1512-1513            1514-1515            1516-1517            1518-1519            1520-1521            1522-1523            1524-1525            1526-1527            1528-1529            1530-1531            1532-1533            1534-1535            1536-1537            1538-1539            1540-1541            1542-1543            1544-1545            1546-1547            1548-1549            1550-1551            1552-1553            1554-1555            1556-1557            1558-1559            1560-1561            1562-1563            1564-1565            1566-1567            1568-1569            1570-1571            1572-1573            1574-1575            1576-1577            1578-1579            1580-1581            1582-1583            1584-1585            1586-1587            1588-1589            1590-1591            1592-1593            1594-1595            1596-1597            1598-1599            1600-1601            1602-1603            1604-1605            1606-1607            1608-1609            1610-1611            1612-1613            1614-1615            1616-1617            1618-1619            1620-1621            1622-1623            1624-1625            1626-1627            1628-1629            1630-1631            1632-1633            1634-1635            1636-1637            1638-1639            1640-1641            1642-1643            1644-1645            1646-1647            1648-1649            1650-1651            1652-1653            1654-1655            1656-1657            1658-1659            1660-1661            1662-1663            1664-1665            1666-1667            1668-1669            1670-1671            1672-1673            1674-1675            1676-1677            1678-1679            1680-1681            1682-1683            1684-1685            1686-1687            1688-1689            1690-1691            1692-1693            1694-1695            1696-1697            1698-1699            1700-1701            1702-1703            1704-1705            1706-1707            1708-1709            1710-1711            1712-1713            1714-1715            1716-1717            1718-1719            1720-1721            1722-1723            1724-1725            1726-1727            1728-1729            1730-1731            1732-1733            1734-1735            1736-1737            1738-1739            1740-1741            1742-1743            1744-1745            1746-1747            1748-1749            1750-1751            1752-1753            1754-1755            1756-1757            1758-1759            1760-1761            1762-1763            1764-1765            1766-1767            1768-1769            1770-1771            1772-1773            1774-1775            1776-1777            1778-1779            1780-1781            1782-1783            1784-1785            1786-1787            1788-1789            1790-1791            1792-1793            1794-1795            1796-1797            1798-1799            1800-1801            1802-1803            1804-1805            1806-1807            1808-1809            1810-1811            1812-1813            1814-1815            1816-1817            1818-1819            1820-1821            1822-1823            1824-1825            1826-1827            1828-1829            1830-1831            1832-1833            1834-1835            1836-1837            1838-1839            1840-1841            1842-1843            1844-1845            1846-1847            1848-1849            1850-1851            1852-1853            1854-1855            1856-1857            1858-1859            1860-1861            1862-1863            1864-1865            1866-1867            1868-1869            1870-1871            1872-1873            1874-1875            1876-1877            1878-1879            1880-1881            1882-1883            1884-1885            1886-1887            1888-1889            1890-1891            1892-1893            1894-1895            1896-1897            1898-1899            1900-1901            1902-1903            1904-1905            1906-1907            1908-1909            1910-1911            1912-1913            1914-1915            1916-1917            1918-1919            1920-1921            1922-1923            1924-1925            1926-1927            1928-1929            1930-1931            1932-1933            1934-1935            1936-1937            1938-1939            1940-1941            1942-1943            1944-1945            1946-1947            1948-1949            1950-1951            1952-1953            1954-1955            1956-1957            1958-1959            1960-1961            1962-1963            1964-1965            1966-1967            1968-1969            1970-1971            1972-1973            1974-1975            1976-1977            1978-1979            1980-1981            1982-1983            1984-1985            1986-1987            1988-1989            1990-1991            1992-1993            1994-1995            1996-1997            1998-1999            2000-2001            2002-2003            2004-2005            2006-2007            2008-2009            2010-2011            2012-2013            2014-2015            2016-2017            2018-2019            2020-2021            2022-2023            2024-2025            2026-2027            2028-2029            2030-2031            2032-2033            2034-2035            2036-2037            2038-2039            2040-2041            2042-2043            2044-2045            2046-2047            2048-2049            2050-2051            2052-2053            2054-2055            2056-2057            2058-2059            2060-2061            2062-2063            2064-2065            2066-2067            2068-2069            2070-2071            2072-2073            2074-2075            2076-2077            2078-2079            2080-2081            2082-2083            2084-2085            2086-2087            2088-2089            2090-2091            2092-2093            2094-2095            2096-2097            2098-2099            2100-2101            2102-2103            2104-2105            2106-2107            2108-2109            2110-2111            2112-2113            2114-2115            2116-2117            2118-2119            2120-2121            2122-2123            2124-2125            2126-2127            2128-2129            2130-2131            2132-2133            2134-2135            2136-2137            2138-2139            2140-2141            2142-2143            2144-2145            2146-2147            2148-2149            2150-2151            2152-2153            2154-2155            2156-2157            2158-2159            2160-2161            2162-2163            2164-2165            2166-2167            2168-2169            2170-2171            2172-2173            2174-2175            2176-2177            2178-2179            2180-2181            2182-2183            2184-2185            2186-2187            2188-2189            2190-2191            2192-2193            2194-2195            2196-2197            2198-2199            2200-2201            2202-2203            2204-2205            2206-2207            2208-2209            2210-2211            2212-2213            2214-2215            2216-2217            2218-2219            2220-2221            2222-2223            2224-2225            2226-2227            2228-2229            2230-2231            2232-2233            2234-2235            2236-2237            2238-2239            2240-2241            2242-2243            2244-2245            2246-2247            2248-2249            2250-2251            2252-2253            2254-2255            2256-2257            2258-2259            2260-2261            2262-2263            2264-2265            2266-2267            2268-2269            2270-2271            2272-2273            2274-2275            2276-2277            2278-2279            2280-2281            2282-2283            2284-2285            2286-2287            2288-2289            2290-2291            2292-2293            2294-2295            2296-2297            2298-2299            2300-2301            2302-2303            2304-2305            2306-2307            2308-2309            2310-2311            2312-2313            2314-2315            2316-2317            2318-2319            2320-2321            2322-2323            2324-2325            2326-2327            2328-2329            2330-2331            2332-2333            2334-2335            2336-2337            2338-2339            2340-2341            2342-2343            2344-2345            2346-2347            2348-2349            2350-2351            2352-2353            2354-2355            2356-2357            2358-2359            2360-2361            2362-2363            2364-2365            2366-2367            2368-2369            2370-2371            2372-2373            2374-2375            2376-2377            2378-2379            2380-2381            2382-2383            2384-2385            2386-2387            2388-2389            2390-2391            2392-2393            2394-2395            2396-2397            2398-2399            2400-2401            2402-2403            2404-2405            2406-2407            2408-2409            2410-2411            2412-2413            2414-2415            2416-2417            2418-2419            2420-2421            2422-2423            2424-2425            2426-2427            2428-2429            2430-2431            2432-2433            2434-2435            2436-2437            2438-2439            2440-2441            2442-2443            2444-2445            2446-2447            2448-2449            2450-2451            2452-2453            2454-2455            2456-2457            2458-2459            2460-2461            2462-2463            2464-2465            2466-2467            2468-2469            2470-2471            2472-2473            2474-2475            2476-2477            2478-2479            2480-2481            2482-2483            2484-2485            2486-2487            2488-2489            2490-2491            2492-2493            2494-2495            2496-2497            2498-2499            2500-2501            2502-2503            2504-2505            2506-2507            2508-2509            2510-2511            2512-2513            2514-2515            2516-2517            2518-2519            2520-2521            2522-2523            2524-2525            2526-2527            2528-2529            2530-2531            2532-2533            2534-2535            2536-2537            2538-2539            2540-2541            2542-2543            2544-2545            2546-2547            2548-2549            2550-2551            2552-2553            2554-2555            2556-2557            2558-2559            2560-2561            2562-2563            2564-2565            2566-2567            2568-2569            2570-2571            2572-2573            2574-2575            2576-2577            2578-2579            2580-2581            2582-2583            2584-2585            2586-2587            2588-2589            2590-2591            2592-2593            2594-2595            2596-2597            2598-2599            2600-2601            2602-2603            2604-2605            2606-2607            2608-2609            2610-2611            2612-2613            2614-2615            2616-2617            2618-2619            2620-2621            2622-2623            2624-2625            2626-2627            2628-2629            2630-2631            2632-2633            2634-2635            2636-2637            2638-2639            2640-2641            2642-2643            2644-2645            2646-2647            2648-2649            2650-2651            2652-2653            2654-2655            2656-2657            2658-2659            2660-2661            2662-2663            2664-2665            2666-2667            2668-2669            2670-2671            2672-2673            2674-2675            2676-2677            2678-2679            2680-2681            2682-2683            2684-2685            2686-2687            2688-2689            2690-2691            2692-2693            2694-2695            2696-2697            2698-2699            2700-2701            2702-2703            2704-2705            2706-2707            2708-2709            2710-2711            2712-2713            2714-2715            2716-2717            2718-2719            2720-2721            2722-2723            2724-2725            2726-2727            2728-2729            2730-2731            2732-2733            2734-2735            2736-2737            2738-2739            2740-2741            2742-2743            2744-2745            2746-2747            2748-2749            2750-2751            2752-2753            2754-2755            2756-2757            2758-2759            2760-2761            2762-2763            2764-2765            2766-2767            2768-2769            2770-2771            2772-2773            2774-2775            2776-2777            2778-2779            2780-2781            2782-2783            2784-2785            2786-2787            2788-2789            2790-2791            2792-2793            2794-2795            2796-2797            2798-2799            2800-2801            2802-2803            2804-2805            2806-2807            2808-2809            2810-2811            2812-2813            2814-2815            2816-2817            2818-2819            2820-2821            2822-2823            2824-2825            2826-2827            2828-2829            2830-2831            2832-2833            2834-2835            2836-2837            2838-2839            2840-2841            2842-2843            2844-2845            2846-2847            2848-2849            2850-2851            2852-2853            2854-2855            2856-2857            2858-2859            2860-2861            2862-2863            2864-2865            2866-2867            2868-2869            2870-2871            2872-2873            2874-2875            2876-2877            2878-2879            2880-2881            2882-2883            2884-2885            2886-2887            2888-2889            2890-2891            2892-2893            2894-2895            2896-2897            2898-2899            2900-2901            2902-2903            2904-2905            2906-2907            2908-2909            2910-2911            2912-2913            2914-2915            2916-2917            2918-2919            2920-2921            2922-2923            2924-2925            2926-2927            2928-2929            2930-2931            2932-2933            2934-2935            2936-2937            2938-2939            2940-2941            2942-2943            2944-2945            2946-2947            2948-2949            2950-2951            2952-2953            2954-2955            2956-2957            2958-2959            2960-2961            2962-2963            2964-2965            2966-2967            2968-2969            2970-2971            2972-2973            2974-2975            2976-2977            2978-2979            2980-2981            2982-2983            2984-2985            2986-2987            2988-2989            2990-2991            2992-2993            2994-2995            2996-2997            2998-2999            3000-3001            3002-3003            3004-3005            3006-3007            3008-3009            3010-3011            3012-3013            3014-3015            3016-3017            3018-3019            3020-3021            3022-3023            3024-3025            3026-3027            3028-3029            3030-3031            3032-3033            3034-3035            3036-3037            3038-3039            3040-3041            3042-3043            3044-3045            3046-3047            3048-3049            3050-3051            3052-3053            3054-3055            3056-3057            3058-3059            3060-3061            3062-3063            3064-3065            3066-3067            3068-3069            3070-3071            3072-3073            3074-3075            3076-3077            3078-3079            3080-3081            3082-3083            3084-3085            3086-3087            3088-3089            3090-3091            3092-3093            3094-3095            3096-3097            3098-3099            3100-3101            3102-3103            3104-3105            3106-3107            3108-3109            3110-3111            3112-3113            3114-3115            3116-3117            3118-3119            3120-3121            3122-3123            3124-3125            3126-3127            3128-3129            3130-3131            3132-3133            3134-3135            3136-3137            3138-3139            3140-3141            3142-</p>					

## Appendix C – Surface Water Calculations

**PRELIMINARY SURFACE WATER STORAGE ESTIMATE (LONG TERM STORAGE PROV)**

**Catchment Characteristics**

**Greenfield Runoff Flows (Sites < 50 Ha)**

denotes Input Value

Standard Average Annual Rainfall (SAAR) =					818	mm
Soil Index =					0.335	
Total Site Area =					0.0290	Hectares (ha)
Storm Return Period =					30	Years
Permissible Outflow per hectare, QBAR =					2.8	l/s/ha
* Total Permissible Outflow=					0.08	l/s
Proposed Impermeable Area:						
	Hardstanding				0.0000	ha
	Roofs				0.0355	ha
	Proposed Open Space					ha

Soil Classification for Runoff Potential

Based on FSR Maps

Soil 1	0	%	↑ Infiltration
Soil 2	50	%	
Soil 3	50	%	
Soil 4	0	%	
Soil 5	0	%	
	@	80	% Impermeable
	@	95	% Impermeable
	@	33.5	% Impermeable

**Rainfall Intensity from Met Eireann**

1 hectare = 10,000m<sup>2</sup>

**0.080575619**

return period      grow curve factor

1	0.85
10	1.7
30	2.1
100	2.6
200	2.9

Duration (min)	Rainfall 1/30 (mm)	Intensity (mm/hr)	Factored Intensity *** (mm/hr)	Factored Rainfall *** (mm)	Rainfall (m <sup>3</sup> /ha)	Volume (m <sup>3</sup> )	Permissible Outflow (m <sup>3</sup> )	Storage Required (m <sup>3</sup> )
5	9.9	118.8	142.6	11.9	118.8	4	0	4
10	13.8	82.8	99.4	16.6	165.6	6	0	6
15	16.2	64.8	77.8	19.4	194.4	7	0	7
30	20.3	40.6	48.7	24.4	243.6	8	0	8
60	25.5	25.5	30.6	30.6	306.0	10	0	10
120	31.9	16.0	19.1	38.3	382.8	13	0	13
180	36.4	12.1	14.6	43.7	436.8	15	0	15
240	39.9	10.0	12.0	47.9	478.8	16	0	16
360	45.5	7.6	9.1	54.6	546.0	18	0	18
540	51.9	5.8	6.9	62.3	622.8	21	0	21
720	57.0	4.8	5.7	68.4	684.0	23	0	23
1080	65.0	3.6	4.3	78.0	780.0	26	0	26
1440	71.4	3.0	3.6	85.7	856.8	29	0	29
2880	81.1	1.7	2.0	97.3	973.2	33	0	33
4320	89.5	1.2	1.5	107.4	1074.0	36	0	36

Value of storage required = **36** m<sup>3</sup>      h      1.5 area      24.15 L1      20.00 L2

**Notes**

\*Total Permissible Outflow calculated in accordance with GSDSDS - Regional Drainage Policies (Volume 2 - Chapter 6)

\*\*Permissible Outflow per Hectare multiplied by growth factors  
i.e. QBAR(m<sup>3</sup>/s)=0.00108x(Area)<sup>0.89</sup>(SAAR)<sup>1.17</sup>(SOIL)<sup>2.17</sup>

SOIL : Soil Index Values in range 0.15-0.5 of Catchment values Available from the FSR. The Index derived from:  
(0.15Soil 1+ 0.30Soil 2 + 0.40Soil 3+ 0.45Soil 4+ 0.50Soil 5)  
(Soil 1+ Soil 2+ Soil 3+ Soil 4+Soil 5)

\*\*\* Rainfall Intensity increased by 20% to comply with global warming effects as described in the GSDSDS - Regional Drainage Policies (Volume 2 - Section 6.3.2.4 - Table 6.2)

**Oversized Pipe Requirements for On-line Storage**

Pipe dia.	Length
(mm)	(m)
2100	10
1500	20
1200	32
1050	42
900	57

**PRELIMINARY SURFACE WATER STORAGE ESTIMATE (LONG TERM STORAGE PROV)**

**Catchment Characteristics**      **Greenfield Runoff Flows (Sites < 50 Ha)**       denotes Input Value

Standard Average Annual Rainfall (SAAR) =					818	mm
Soil Index =					0.335	
Total Site Area =					0.1930	Hectares (ha)
Storm Return Period =					30	Years
Permissible Outflow per hectare, QBAR =					2.8	l/s/ha
* Total Permissible Outflow=					0.54	l/s
Proposed Impermeable Area:						
	Hardstanding				0.1930	ha
	Roofs				0.0000	ha
	Proposed Open Space					ha

Soil Classification for Runoff Potential

Based on FSR Maps

Soil 1	0	%	↑ Infiltration
Soil 2	50	%	
Soil 3	50	%	
Soil 4	0	%	
Soil 5	0	%	

.....@	80	% Impermeable
.....@	95	% Impermeable
.....@	33.5	% Impermeable

**Rainfall Intensity from Met Eireann**

1 hectare = 10,000m<sup>2</sup>

return      grow curve

period      factor

1	0.85
10	1.7
30	2.1
100	2.6
200	2.9

Duration (min)	Rainfall 1/30 (mm)	Intensity (mm/hr)	Factored Intensity *** (mm/hr)	Factored Rainfall *** (mm)	Rainfall (m <sup>3</sup> /ha)	Volume (m <sup>3</sup> )	Permissible Outflow (m <sup>3</sup> )	Storage Required (m <sup>3</sup> )
5	9.9	118.8	142.6	11.9	118.8	18	0	18
10	13.8	82.8	99.4	16.6	165.6	26	0	26
15	16.2	64.8	77.8	19.4	194.4	30	0	30
30	20.3	40.6	48.7	24.4	243.6	38	0	38
60	25.5	25.5	30.6	30.6	306.0	47	0	47
120	31.9	16.0	19.1	38.3	382.8	59	0	59
180	36.4	12.1	14.6	43.7	436.8	67	0	67
240	39.9	10.0	12.0	47.9	478.8	74	0	74
360	45.5	7.6	9.1	54.6	546.0	84	0	84
540	51.9	5.8	6.9	62.3	622.8	96	0	96
720	57.0	4.8	5.7	68.4	684.0	106	0	106
1080	65.0	3.6	4.3	78.0	780.0	120	0	120
1440	71.4	3.0	3.6	85.7	856.8	132	0	132
2880	81.1	1.7	2.0	97.3	973.2	150	0	150
4320	89.5	1.2	1.5	107.4	1074.0	166	0	166

**Value of storage required =** 166 m<sup>3</sup>      h      1.5 area      110.55 L1      20.00 L2

**Notes**

\*Total Permissible Outflow calculated in accordance with GSDSDS - Regional Drainage Policies (Volume 2 - Chapter 6)

\*\*Permissible Outflow per Hectare multiplied by growth factors  
i.e. QBAR(m<sup>3</sup>/s)=0.00108x(Area)<sup>0.89</sup>(SAAR)<sup>1.17</sup>(SOIL)<sup>2.17</sup>

SOIL : Soil Index Values in range 0.15-0.5 of Catchment values Available from the FSR. The Index derived from:  
(0.15Soil 1+ 0.30Soil 2 + 0.40Soil 3+ 0.45Soil 4+ 0.50Soil 5)  
(Soil 1+ Soil 2+ Soil 3+ Soil 4+Soil 5)

\*\*\* Rainfall Intensity increased by 20% to comply with global warming effects as described in the GSDSDS - Regional Drainage Policies (Volume 2 - Section 6.3.2.4 - Table 6.2)

**Oversized Pipe Requirements for On-line Storage**

Pipe dia.	Length
(mm)	(m)
2100	48
1500	94
1200	147
1050	192
900	261